

Ultra-thin special washi paper with low adhesive strength for ultra-sharp paint edges, ideal for sensitive surfaces

Application areas

- ideal for particularly sensitive surfaces (wallpapers, freshly coated surfaces, wall coverings, unvarnished wood)
- especially suitable for special applications, painters, joint specialists, handicraft etc.

Product benefits



- ensures precise color edges and prevents paint and varnish seepage at edges and transitions
- easy to unwind and comfortable to work with
- good temperature stability until 80 °C
- residue-free removable
- for indoor and outdoor use (until 30 days in the outdoor area)

Base

Tape: impregnated washi rice paper (purple)
Adhesive: acrylate dispersion

Tape thickness

ca. 0.09 mm

Bond strength

very low

Temperature resistance

for a short time up to +80 °C

UV resistance

max. 30 days

Colour

purple

Standard stock dimensions

Item no.	Width	Packing Unit	MOQ*
AB 7025.36	25 mm	36 rolls x 50 m = 2400 m	9 rolls

*MOQ = minimum order quantity (1 shrink pack)

Further information



More information about this product (current technical data sheet, safety data sheet, certificates, product variants, etc.) can be found via the adjacent QR code.

Shelf life

In closed original packaging, protected from direct sunlight, stored in a dry place between +15 °C and +25 °C and optimum humidity between 40 % and 60 %, the official shelf life is at least 24 months from date of production.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.