


Transfer adhesive tape; thin, double-sided self-adhesive mounting tape, strong adhesive and versatile in use

Application areas	Top of the range transfer tape with versatile application possibilities <ul style="list-style-type: none">▪ especially for film, elastic materials (even large parts) or hard small parts▪ for the «self-adhesive finishing» of wood, plastic, metal etc.▪ ideal for handicraft and industry
Product benefits	<ul style="list-style-type: none">▪ double-sided self-adhesive▪ very good resistance to ageing, condensation water, plasticisers and temperature▪ high adhesive strength▪ good shear strength▪ transparent▪ insensitive to moisture▪ complies with DIN EN ISO 846:2019 method A (fungus resistance) and method C (bacteria resistance)▪ meets the requirements of VDI 6022(1):2018 for air conditioning systems
Base	Adhesive carrier: polyester film Adhesive: UV curable hot melt adhesive based on acrylate Intermediate film: yellow silicone paper
Restrictions	Due to the small thickness, stress levelling is limited. If necessary, use elastic mounting adhesive or suitable, thicker adhesive tape, e.g. Wikofix SKB 490 mirror adhesive tape.
Processing	The substrate must be sound, dry and free of dust and grease. Stick the adhesive tape precisely onto the substrate, remove the protective film and fix the second part to be joined onto the tape with sufficient pressure.
Temperature resistance	from -30 °C up to +120 °C, for a short time up to +150 °C (adhesive)
Adhesive strength	min. 15 N/25 mm (acc. to DIN 1939-C)
Shear strength	min. 70 N/cm ² (dynamic, in-house method)
Tape thickness	ca. 0.14 mm (acc. to ISO 845)
Further information	 More information about this product (current technical data sheet, safety data sheet, certificates, product variants, etc.) can be found via the adjacent QR code.
Colours	transparent

Standard stock dimensions

Item no.	Width	Packing Unit
DSK 88.06	6 mm	50 rolls of 50 m = 2500 m
DSK 88.09	9 mm	33 rolls of 50 m = 1650 m
DSK 88.12	12 mm	25 rolls of 50 m = 1250 m
DSK 88.15	15 mm	20 rolls of 50 m = 1000 m
DSK 88.19	19 mm	15 rolls of 50 m = 750 m
DSK 88.25	25 mm	12 rolls of 50 m = 600 m
DSK 88.30	30 mm	10 rolls of 50 m = 500 m
DSK 88.38	38 mm	8 rolls of 50 m = 400 m
DSK 88.50	50 mm	6 rolls of 50 m = 300 m

good to know...

Each roll is wrapped individually!

Special dimensions

Other widths from 6 to 1000 mm or other roll lengths possible with corresponding quantities.

Shelf life

In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.