

Transparent, dirt-repellent protective coating for paint sealants (MS-polymer, polyurethane or acrylic)

Application areas	Colourless, scrub-resistant and glossy coating ▪ for coatable joints indoors ▪ optimal for hybrid sealants (MS Polymer, STP, SPUR and other silane-modified polymers), polyurethanes and acrylates
Product benefits	▪ recoatable ▪ good compatibility with emulsion paints, plastering, concrete and similar substrates (also large surface area) ▪ solvent-free (VOC-free)
Base	acrylate dispersion
Cleaning agents	Wisatyp TL 16 for cleaning non-absorbent adhesive surfaces and fresh product residues. The cured product can normally only be removed mechanically. Wash hands and tools with clean water.
Processing	The substrate must be sound, dry and free of dust and grease. Recommendation: Clean joints beforehand with Wisatyp TL 16 (this cleaner also removes any smoothing agent residues). Mask / cover the joint edge and areas not to be treated, as the dried protective layer is difficult to remove. Apply the protective coating with a suitable brush and allow to dry. Apply a second coat if necessary. The gloss level of Wikofix Joint Protection can be reduced to silk matt if the product is diluted with water up to a maximum of 1:1 before application.
Density	ca. 1.0 g/cm ³
pH-value	7 - 8
Processing temperature	from +5 °C up to +40 °C
Consumption	ca. 100 - 150 ml/m ² per coating 250 ml sufficient for ca. 200 m joint (10 mm joint width)
Further information	 More information about this product (current technical data sheet, safety data sheet, certificates, product variants, etc.) can be found via the adjacent QR code.
Item no. + Colour	FS 25.250 colourless-transparent (whitish when still wet)
Delivery form	Packing unit of 15 PE bottles of 250 ml Further containers on request.
Shelf life	In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

Safety and disposal: Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.