

Moisturising fluid for smoothing freshly applied sealants based on silicone, polyurethane and MS polymers

Application areas	Smoothing agent concentrate <ul style="list-style-type: none">▪ for wetting and smoothing freshly sprayed sealants▪ optimal for silicones, hybrid sealants (MS Polymer, STP, SPUR and other silane-modified polymers) as well as polyurethanes▪ also used as an aid when pressing the rubber gaskets into the window profiles
Product benefits	<ul style="list-style-type: none">▪ good lubricating properties▪ gentle on the skin▪ solvent-free (VOC-free)▪ biodegradable▪ neutral odour▪ pH-neutral▪ phosphate free
Base	aqueous concentrate based on modified plant extracts
Restrictions	Not suitable for Acryl-Dichtstoffe and other water-based sealing compounds. For sensitive substrates, such as wallpaper that cannot be washed
Processing	Depending on the type of sealant, mix 5% to a max. of 10% Wikofix GM 52 smoothing concentrate into fresh water. Shake the mixture well, spray on and smooth off. Use a smoothing spatula for finishing / leveling. Remove residues and runs as quickly as possible with clean water. The mixture can be used for several days.
Density	ca. 1.0 g/cm ³
pH-value	7 - 8 (pH-neutral)
Processing temperature	+5 °C up to +50 °C
Cleaning agents	Wash hands and, if necessary, adjacent surfaces with clean water.
Further information	 More information about this product (current technical data sheet, safety data sheet, certificates, product variants, etc.) can be found via the adjacent QR code.
Item no. + Delivery form	GM 52.500 colourless-transparent Packing unit of 12 PE bottles of 500 ml Further containers on request.
Shelf life	In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 12 months from date of production (the printed expiry date is decisive).

Accessories	TG 52.3110	Manual atomiser 600 ml
	TG 52.3111	Manual atomiser 900 ml display (content 1 liter)

Safety and disposal: Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.