

## Concentrate for fast and thorough removal of wallpaper

<b>Application areas</b>	Well-suited for removing old glue-bound paints from: <ul style="list-style-type: none"> <li>▪ paper wallpapers</li> <li>▪ textile wallpapers</li> <li>▪ vinyl wallpapers</li> <li>▪ ingrain wallpaper</li> </ul>
<b>Product benefits</b>	<ul style="list-style-type: none"> <li>▪ highly effective</li> <li>▪ rapid penetration of wallpaper layers</li> <li>▪ environmentally friendly, contains biodegradable surfactants</li> </ul>
<b>Base</b>	concentrate made of non-ionic surfactants, water, and additives
<b>Processing</b>	<p>Carefully cover surfaces not to be treated, such as floors, doors, and furniture. Generously apply the solution to the wallpaper using a ceiling brush. After allowing sufficient time to take effect, the wallpaper can be easily removed. For stubborn wallpapers, repeat the application two to three times, wet-on-wet. Before treatment, roughen water-resistant, washable wallpapers using a spiked roller or coarse sandpaper to enhance the effect of the solution. Thoroughly clean work tools with water after use. Any remaining residue from the wallpaper remover can be easily washed away with water.</p> <p>Remark: To remove uncoated wallpaper, dilute 250 ml of wallpaper remover in 15 liters of water. For vinyl or coated wallpaper, mix 250 ml of wallpaper remover with approx. 8–10 liters of water to achieve optimal effectiveness. Seal open containers well for further storage.</p>
<b>Density</b>	ca. 1.0 g/cm <sup>3</sup>
<b>pH-value</b>	7 - 8
<b>Processing temperature</b>	from +5 °C up to +40 °C
<b>Consumption</b>	250 ml sufficient for ca. 50 - 100 m <sup>2</sup> depending on the dilution and amount applied
<b>Further information</b>	<div style="display: flex; align-items: center;">  <p>You can find more information about this product (link to the product on our homepage, safety data sheet, certificates, special enquiries etc.) under the adjacent ISOPIN QR code.</p> </div>
<b>Item no. + Colour</b>	<b>TA 520.5</b> PE can of 5 l
<b>Delivery form</b>	<b>TA 520.10.</b> PE can of 10 l
	<b>transparent (yellowish)</b> Further containers on request.

## Shelf life

Protect from frost! In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 36 months from date of production (the printed expiry date is decisive).

**Safety and disposal:** Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

**Observe:** All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at [www.wisabax.ch/agb.html](http://www.wisabax.ch/agb.html). © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.