

PVC cleaner, slightly soluble, low odour, for preparation of bonded surfaces before bonding with PVC adhesives

Application areas

Low-dissolving, antistatic cleaner

- for white PVC rigid profiles (e.g. plastic (PVC) window construction)
- for preparing the bonding surfaces before gluing (cold-welding) with Wisacoll TH 301 transparent, Wisacoll TH 312 white and Wisacoll TH 341
- for removing stubborn soiling and markings on PVC hard-white, after prior cleaning with Wisaclean R 202
- for removing pencil and felt-tip pen marks, metal abrasion, rust, paint and rubber marks
- for various non-transparent thermoplastics and thermosets
- exclusively for professional applications

Product benefits

- weakly dissolving
- optimum preparation of rigid PVC before cold welding
- low odour
- antistatic
- high cleaning performance
- quick-drying
- leaves no film or other substances
- no impairment of the weather fastness of cleaned PVC profiles

Base

aliphatic ketones and hydrocarbons

Restrictions

- Not suitable for lacquered surfaces, laminated surfaces and plastics prone to stress cracking such as e.g. PMMA.
- Use the non-dissolving cleaner Wisaclean R 202 to remove dust, adhesive residues from the protective films and fresh PUR and silicone residues.
- For consequential damage caused by improper use, particularly repeated use after window installation, we accept no liability.
- Due to the hygroscopic effect of dissolved PVC, dissolvers should only be used in dry climates.

Self-tests

Due to the wide variety of surfaces and color formulations used in the field, in-house testing is required.

Processing

The surface to be cleaned must be dry and dust-free.
Otherwise, pre-clean the plastic with the non-dissolving cleaner Wisaclean R 202, especially on very dusty surfaces.

Only use a dry, lint-free, non-staining cloth, cotton or pulp for cleaning. For this purpose, we recommend Wisaclean cleaning paper RP 2033.12.
Change the cleaning paper, cloth or similar regularly to prevent dirt residues from being carried over.

Keep out of direct sunlight and protect from UV radiation during application.

Due to the weak corrosive effect on PVC-hard, intensive treatment or exposure time should be avoided.

As a rule, a single wipe over the surface of the material to be cleaned will be sufficient. In the case of heavier soiling, the cleaning process can be repeated after REHARDENING the material surfaces. For polishing and repair work, the highly soluble polishing agent Wisatyp RP 55 is available.

Avoid direct skin contact with the cleaner. Seal open containers tightly for further storage. Our Wisaclean solvent-saving dispensers are proven for stationary use (see accessories).

This product is for specialist trained personnel.

Density	ca. 0.76 g/ml (at 20 °C)
Consistency	liquid
Processing temperature	from +5 °C up to +30 °C
Flash point	-14 °C
Transport restrictions	UN 1993 - dangerous goods according to ADR, RID, ADN, IMDG, IATA Special transport regulations apply for canisters. shipping in Switzerland: Bottles are subject to the Limited Quantities Ordinance and can be delivered by parcel service.

Further information



You can find more information about this product (link to the product on our homepage, safety data sheet, certificates, special enquiries etc.) under the adjacent ISOPIN QR code.

**Item no. +
Delivery form**

PR 114.1000
packing unit of 10 tinplate bottles of 1000 ml
Further containers on request.

PR 114.10.
tinplate cans of 10 l
Sending of canisters by post is prohibited.

Shelf life
In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

Accessories	Item no.	Brief description
good to know...	TR 100.04	Wisaclean solvent-saving dispenser: 4 litre safety container for the stationary use of non-aqueous cleaners and solvents <ul style="list-style-type: none">▪ saves solvent through one-sided wetting▪ protects people and the environment (less vapours)▪ saves time and money▪ amortises after a short time
	RP 2033.12	Wisaclean cleaning paper: white, neither linting nor discolouring, made of 100 % cellulose, two-ply, perforated, embossed, sturdy. On practical small rolls. Delivery form = 12 rolls of approx. 210 sheets each 33x20 cm (LxW)

Safety and disposal: Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.