

## Mild, particularly easy to dissolve PVC-hard cleaner, approved for window installation

- Application areas**
- for cleaning of white PVC hard profiles during window and door installation
  - for removing pencil and felt-tip pen marks, metal abrasion, rust, paint and rubber marks
  - for various non-transparent thermoplastics and thermosets
  - exclusively for professional applications (plastic (PVC) window construction etc.)
- Product benefits**
- particularly easy dissolving
  - antistatic
  - high cleaning performance
  - quick-drying
  - leaves no film or other substances
- Base** solvent mixture
- Restrictions**
- Not suitable for lacquered surfaces, laminated surfaces and plastics prone to stress cracking such as e.g. PMMA.
  - For consequential damage caused by improper use, particularly repeated use after window installation, we accept no liability.
  - Due to the hygroscopic effect of dissolved PVC, dissolvers should only be used in dry climates.
- Self-tests** Due to the wide variety of surfaces and color formulations used in the field, in-house testing is required.
- Processing** This product is for specialist trained personnel.
- The surface to be cleaned must be dry and dust-free. Otherwise, pre-clean the plastic with the non-dissolving cleaner Wisaclean R 202, especially on very dusty surfaces.
- Only use a dry, lint-free, non-staining cloth, cotton or pulp for cleaning. For this purpose, we recommend Wisaclean cleaning paper RP 2033.12. Change the cleaning paper, cloth or similar regularly to prevent dirt residues from being carried over.
- Keep out of direct sunlight and protect from UV radiation during application. Due to the slightly corrosive effect on PVC-hard, intensive treatment or exposure time should be avoided.
- As a rule, a single wipe over the surface of the material to be cleaned will be sufficient. In the case of heavier soiling, the cleaning process can be repeated after REHARDENING the material surfaces.
- Avoid direct skin contact with the cleaner. Tightly close opened containers for further storage. Our Wisaclean solvent-saving dispensers are proven for stationary use (see accessories).

<b>Density</b>	ca. 0.75 g/ml (at 20 °C)
<b>Consistency</b>	liquid
<b>Processing temperature</b>	from +5 °C up to +30 °C
<b>Flash point</b>	-14 °C
<b>Transport restrictions</b>	UN 1993 - dangerous goods according to ADR, RID, ADN, IMDG, IATA Special transport regulations apply for canisters. Shipping in Switzerland: The cans comply with the restricted quantities regulation and can be delivered by parcel service.

**Further information**



You can find more information about this product (link to the product on our homepage, safety data sheet, certificates, special enquiries etc.) under the adjacent ISOPIN QR code.

<b>Item no. + Delivery form</b>	<b>PR 204.1000</b> carton box of 10 doses à 1000 ml	Further containers on request.
	<b>PR 204.10</b> - canisters à 10 liter Sending of canisters by post is prohibited.	

**Shelf life** In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

<b>Accessories</b>	<b>Item no.</b>	<b>Brief description</b>
<b>good to know...</b>	<b>TR 100.04</b>	<b>Wisaclean solvent-saving dispenser:</b> 4 litre safety container for the stationary use of non-aqueous cleaners and solvents <ul style="list-style-type: none"> <li>saves solvent through one-sided wetting</li> <li>protects people and the environment (less vapours)</li> <li>saves time and money</li> <li>amortises after a short time</li> </ul>
	<b>RP 2033.12</b>	<b>Wisaclean cleaning paper:</b> White, neither linting nor discolouring, made of 100 % cellulose, two-ply, perforated, embossed, sturdy. On practical small rolls. Delivery form = 12 rolls of approx. 210 sheets each 33x20 cm (LxW)

**Safety and disposal:** Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

**Observe:** All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at [www.wisabax.ch/agb.html](http://www.wisabax.ch/agb.html). © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.