

## Soft, fast and versatile solvent-based cleaner and degreaser

<b>Application areas</b>	<ul style="list-style-type: none"><li>▪ for cleaning and degreasing before bonding and sealing</li><li>▪ for removing fresh adhesive and sealant residues as well as fresh PUR foam</li><li>▪ removes dust, grease, rubber traces, tar and adhesive residues from protective foils</li><li>▪ for cleaning painted, treated and untreated surfaces of all types, especially metals</li><li>▪ for delicate plastics that are prone to stress cracking, e.g. acrylic glass (PMMA)</li><li>▪ in window and door construction for cleaning powder-coated, anodised and PUR profiles</li><li>▪ ideal for all professional users in trade and industry (building craft, window and door construction etc.)</li></ul>
<b>Product benefits</b>	<ul style="list-style-type: none"><li>▪ universal</li><li>▪ quick-drying</li><li>▪ leaves no film or other substances</li><li>▪ no unpleasant odour</li><li>▪ does not attack practically any surfaces</li></ul>
<b>Base</b>	Mixed aliphatic hydrocarbons
<b>Restrictions</b>	For PVC-hard and for plastics that tend to become statically charged when rubbed hard, we offer other options.
<b>Self-tests</b>	<ul style="list-style-type: none"><li>▪ Due to the wide variety of surfaces and color formulations used in the field, in-house testing is required.</li><li>▪ In particular, matt effects can occur with TGIC-free powder coatings.</li><li>▪ If colour pigments are visible in the cleaning cloth when cleaning powder-coated surfaces, this may indicate that the powder coating has not been sufficiently cured. In this case, you should also contact a powder coating expert.</li></ul>
<b>Processing</b>	<p>Only use a dry, lint-free, non-staining cloth, cotton or pulp for cleaning. For this purpose, we recommend Wisaclean cleaning paper RP 2033.12. Change the cleaning paper, cloth or similar regularly to prevent dirt residues from being carried over.</p> <p>Avoid direct skin contact with the cleaner. Seal open containers tightly for further storage. Our Wisaclean solvent-saving dispensers are proven for stationary use (see accessories). This product is for specialist trained personnel.</p>
<b>Density</b>	ca. 0.71 g/ml (at 20 °C)
<b>Consistency</b>	liquid
<b>Processing temperature</b>	from +5 °C up to +30 °C
<b>Flash point</b>	-14 °C

**Transport restrictions** UN 3295 - dangerous goods according to ADR, RID, ADN, IMDG, IATA  
Special transport regulations apply for canisters.  
Shipping in Switzerland: Bottles are subject to the Limited Quantities Ordinance and can be delivered by parcel service.

**Further information**  More information about this product (current technical data sheet, safety data sheet, certificates, product variants, etc.) can be found via the adjacent QR code.

**Item no. + Container sizes** **TR 216.1000**  
Packing unit of 12 tinfoil bottles of 1000 ml  
Further containers on request.

**TR 216.10.**  
Tinfoil cans of 10 l  
Sending of canisters by post is prohibited.

<b>Accessories</b>	<b>Item no.</b>	<b>Brief description</b>
<b>good to know...</b>	<b>TR 100.04</b>	<b>Wisaclean solvent-saving dispenser:</b> 4 litre safety container for the stationary use of non-aqueous cleaners and solvents <ul style="list-style-type: none"><li>▪ saves solvent through one-sided wetting</li><li>▪ protects people and the environment (less vapours)</li><li>▪ saves time and money</li><li>▪ amortises after a short time</li></ul>
	<b>RP 2033.12</b>	<b>Wisaclean cleaning paper:</b> white, neither linting nor discolouring, made of 100 % cellulose, two-ply, perforated, embossed, sturdy. On practical small rolls. Delivery form = 12 rolls of approx. 210 sheets each 33x20 cm (LxW)

**Shelf life** In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

**Safety and disposal:** Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

**Observe:** All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at [www.wisabax.ch/agb.html](http://www.wisabax.ch/agb.html). © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.