

## Solvent and cleaner with long exposure time, dissolves adhesive labels, silicone and film residues

<b>Application areas</b>	<p>Slowly evaporating solvent and cleaning agent designed for professional use:</p> <ul style="list-style-type: none"><li>▪ particularly suitable for self-adhesive label removal</li><li>▪ for cleaning and degreasing most non-absorbent surfaces such as glass, ceramics, metal, PVC-hard and various other plastics</li><li>▪ for the dissolution and removal of thin silicone films or stubborn residue from pressure sensitive adhesives and masking films</li><li>▪ for removing fresh adhesive and sealant residues as well as fresh PUR foam</li><li>▪ removes dust, grease, rubber traces, tar and adhesive residues from protective foils</li><li>▪ ideal for all professional users in trade and industry (building craft, window and door construction etc.)</li></ul>
<b>Product benefits</b>	<ul style="list-style-type: none"><li>▪ particularly slow evaporating</li><li>▪ does not attack practically any surfaces</li></ul>
<b>Base</b>	mixed aliphatic hydrocarbons (flavoured)
<b>Restrictions</b>	For absorbent substrates, the airing time can take several hours. Our range of products offers you a choice.
<b>Self-tests</b>	Due to the wide variety of surfaces and color formulations used in the field, in-house testing is required.
<b>Processing</b>	<p>This product is for specialist trained personnel. Only use a dry, lint-free, non-staining cloth, cotton or pulp for cleaning. For this purpose, we recommend Wisaclean cleaning paper RP 2033.12. Change the cleaning paper, cloth or similar regularly to prevent dirt residues from being carried over.</p> <p>The product is not miscible with water. To remove self-adhesive labels, paint the labels with a soaked brush. Leave on for at least 10 min, longer depending on the label / residues. Repeat the process if necessary. Then carefully remove (peel off) the labels. With long and repeated exposure, thin silicone residues or stubborn residues of pressure-sensitive adhesives and masking films can be dissolved and removed.</p> <p>Tip: To delay evaporation, the surfaces wetted with Wisatyp SA solvent can be covered with a film.</p> <p>Avoid direct skin contact with the cleaner. Seal open containers tightly for further storage. Our Wisaclean solvent-saving dispensers are proven for stationary use (see accessories).</p>
<b>Density</b>	ca. 0.77 g/ml (at 20 °C)
<b>Consistency</b>	liquid

**Processing temperature** from +5 °C up to +30 °C

**Flash point** >30 °C

**Transport restrictions** UN 1300 - dangerous goods according to ADR, RID, ADN, IMDG, IATA  
Special transport regulations apply for canisters.  
Shipping in Switzerland: Bottles are subject to the Limited Quantities Ordinance and can be delivered by parcel service.

**Further information**



You can find more information about this product (link to the product on our homepage, safety data sheet, certificates, special enquiries etc.) under the adjacent ISOPIN QR code.

**Item no. +  
Delivery form**

**TL 1001.1000**

packing unit of 10 tinplate bottles of 1000 ml  
Further containers on request.

**TL 1001.10.**

tinplate cans of 10 l  
Sending of canisters by post is prohibited.

**Shelf life**

In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

**Accessories**

**good to know...**

**Item no.**

**Brief description**

**TR 100.04**

**Wisaclean solvent-saving dispenser:** 4 litre safety container for the stationary use of non-aqueous cleaners and solvents

- saves solvent through one-sided wetting
- protects people and the environment (less vapours)
- saves time and money
- amortises after a short time

**RP 2033.12**

**Wisaclean cleaning paper:** white, neither linting nor discolouring, made of 100 % cellulose, two-ply, perforated, embossed, sturdy. On practical small rolls.  
Delivery form = 12 rolls of approx. 210 sheets each  
33x20 cm (LxW)

**Safety and disposal:** Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

**Observe:** All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at [www.wisabax.ch/agb.html](http://www.wisabax.ch/agb.html). © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.