

Fast and thorough cleaner for most non-absorbent surfaces such as glass, ceramics, metal, etc.

Application areas	Professional, fast evaporating, thorough cleaner <ul style="list-style-type: none">▪ for cleaning and degreasing practically all non-absorbent surfaces before bonding and sealing▪ for cleaning all types of painted, treated and untreated surfaces▪ for removing fresh adhesive and sealant residues as well as fresh PUR foam▪ ideal for all professional users in trade and industry (glass workshops, building craft, window and door construction etc.)
Product benefits	<ul style="list-style-type: none">▪ well mixed with water▪ particularly gentle on stove-enamelled and painted substrates▪ quick-drying▪ leaves no film or other substances▪ does not attack practically any surfaces
Base	hydrophilic solvents
Restrictions	Not suitable for acrylic glass (PMMA), as stress cracks may appear on the surface. For PVC-hard we offer other options.
Self-tests	Due to the many materials and paint formulations used in practice, in-house tests are required, especially for plastics and paints.
Processing	<p>This product is for specialist trained personnel.</p> <p>Only use a dry, lint-free, non-staining cloth, cotton or pulp for cleaning. For this purpose, we recommend Wisaclean cleaning paper RP 2033.12. Change the cleaning paper, cloth or similar regularly to prevent dirt residues from being carried over.</p> <p>Avoid direct skin contact with the cleaner. Tightly close opened containers for further storage. our economical humidifiers are proven for stationary use (see accessories).</p>
Density	ca. 0.79 g/ml (at 20 °C)
Consistency	liquid
Processing temperature	from +5 °C up to +30 °C
Flash point	+12 °C
Ignition temperature	+425 °C
Transport restrictions	UN 1219 - dangerous goods according to ADR, RID, ADN, IMDG, IATA Special transport regulations apply for canisters. shipping in Switzerland: The cans comply with the restricted quantities regulation and can be delivered by parcel service.

Further information



You can find more information about this product (link to the product on our homepage, safety data sheet, certificates, special enquiries etc.) under the adjacent ISOPIN QR code.

Item no. +

TL 2016.1000

Delivery form

carton box of 10 doses à 1000 ml Further containers on request.

TL 2016.10 - canisters à 10 liter

Sending of canisters by post is prohibited.

Accessories

Item no.

Brief description

good to know...

TR 100.04

Wisaclean economy humidifier: 4 litre safety container for the stationary use of non-aqueous cleaners and solvents

- saves solvent through one-sided wetting
- protects people and the environment (less vapours)
- saves time and money
- amortises after a short time

RP 2033.12

Wisaclean cleaning paper: White, neither linting nor discolouring, made of 100 % cellulose, two-ply, perforated, embossed, sturdy. On practical small rolls.

Delivery form = 12 rolls of approx. 210 sheets each 33x20 cm (LxW)

Shelf life

In closed original packaging, protected from direct sunlight and stored in a dry place between +15 °C and +25 °C, the official shelf life is at least 24 months from date of production (the printed expiry date is decisive).

Safety and disposal: Familiarise yourself with the valid Safety Data Sheets (SDS) for the products used. All applicable safety regulations and disposal instructions must be observed.

Observe: All information is based on careful examinations in the labs and our previous practical experience. They are non-committal notes. Due to the many materials that are marketed and the different processing methods, which we cannot influence, we can, of course, not assume any warranty, including under patent-law, for the result of your work. We recommend performing sufficient own tests to find out if the product meets the respective requirements. In addition, we refer to our terms and conditions of sale, delivery and payment, available at www.wisabax.ch/agb.html. © Wisabax AG - This technical data sheet replaces all older versions.

Have you noticed an unclear formulation or an error? Thank you for your feedback. In case of doubt, the German version of the technical data sheet applies.