Wi-Primer V-04

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier


Trade Name	**Wi-Primer V-04**
Item number	PV 1404.120, PV 1404.1000, PV 1404.300
BAG-Register number (CH)	CPID: 119885-22 UFI: R230-J0HS-V00P-V3Y8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Primer
Uses advised against	All applications that are not explained in this technical data sheet.
Field for application [SU]	SU22 – Commercial use: Public domain (administration, education, entertainment, services, trade)

1.3 Details of the supplier of the safety data sheet

Supplier	**Wisabax AG** Kleb- und Dichtstoffe
Address	Grossmatte 21 / Postfach CH-6014 Luzern-Littau
Phone	+41 (0)41 250 18 18
Email	info@wisabax.ch
URL	www.wisabax.ch
Information contact	Technical Dept. - Mr B. Wicki Environment Dept. - Mrs E. Svets



1.4 Emergency telephone number

24h emergency number (just possible in switzerland)	**Tel. 145**
Tox Info Suisse (ancient swiss toxicological infomations centre) **For emergencies from all the countries** 24h accessible in german, french, italian oder english. For not urgent cases see www.toxinfo.ch.	**Tel. +41 (0)44 251 51 51**



2. Hazards identification

2.1 Classification of the substance or mixture according to (EC) Nr. 1272/2008 (CLP).

Hazard class	Hazard category	Hazard warnings
Eye Irrit.	2	H319 Causes serious eye irritation.
STOT SE	3	H336 May cause drowsiness or dizziness.
Flam. Liq.	2	H225 Highly flammable liquid and vapour.

2.2 Labelling according to Regulation (EC) Nr. 1272/2008 (CLP)

Pictograms(e)	 
Signal word(s)	**Danger**
Hazard warning(s) [H-statements]	H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

Safety instruction(s) [P-statements]	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. P241 Use explosion-proof [electrical / ventilating / lighting /…] equipment. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water / shower. P405 Store locked up. P501 Dispose of contents / container to the special waste disposal.
Special marking(s) [EUH-Phrases]	omitted
Contains	omitted

2.3 Other hazards

Persons suffering from allergic reactions to this product should avoid contact with de product.

Results of PBT and vPvB assessment according to Annex XIII of Regulation (EC) No 1907/2006.
PBT: Not applicable vPvB: Not applicable

3. Composition/information on ingredients

3.1 Substances
This product is a mixture, for more see section 3.2.

3.2 Description of the mixture
Mixture of the substances listed below with harmless additions.

Content: 25 % - 50 %

CAS No.: 79-20-9 EG No.: 201-185-2 Index No.: 607-021-00-X Reg. No. (REACH): 01-2119459211-47-XXXX	**methyl acetate**	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE. 3, H336

Content: 25 % - 50 %

CAS No.: 67-64-1 EG No.: 200-662-2 Index No.: 606-001-00-8 Reg. No. (REACH): 01-2119471330-49-XXXX	**acetone** [25/Q59,1/3,4]	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066

Content: 10 % - 20 %

CAS No.: 141-78-6 EG No.: 205-500-4 Index No.: 607-022-00-5 Reg. No. (REACH): 01-2119475103-46-XXXX	**ethyl acetate**	EUH066 ; Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336

Note: H-phrases and abbreviations are detailed in section 16.

4. First aid measures

4.1 Description of first aid measures

General information	Observe the general rules of first aid measures. Refresh occasionally your knowledge. If medical advice is required, have this safety data sheet, the packaging or the label ready.
Following inhalation	Remove affected person from the danger area. Supply fresh air. Loosen restrictive clothing. Place in a resting position. Consult a doctor depending on the symptoms. If not breathing provide immediately artificial respiration and obtain medical

	treatment. In case of unconsciousness bring person in recovery position and take medical advice.
Following skin contact	Remove contaminated clothing immediately. Wash skin with much water and soap. Consult a doctor depending ond the symptoms, if possible, show this container or label.
Following eye contact	Remove contact lenses, if possible. Rinse thoroughly with water and consult a doctor. Present this safety data sheet or product label.
Following ingestion	Rinse mouth thoroughly with water. Keep airways free. Telephone the emergency number or consult a doctor. If it is possible, present this safety data sheet or product label. Do not induce vomiting!

4.2 Most important symptoms and effects, both acute and delayed
In certain cases, symptoms of intoxication may only appear after a longer period of time/after several hours. See section 11.

4.3 Indication of any immediate medical attention and special treatment needed
-

5. Firefighting measures

5.1 Extinguishing media
Always adapt firefighting measures to the surroundings and the size of the fire.

Suitable extinguishing media: Water spray jet, Dry powder fire extinguishers, Alcohol-resistant foam, Carbon dioxide
Unsuitable extinguishing media: Full water jet

5.2 Special hazards arising from the substance or mixture
Combustible. Formation of explosive mixtures possible with air.
Formation of toxic gases is possible during heating or in case of fire:
Carbon oxide. Carbon monoxide.

5.3 Advice for fire-fighters
Do not inhale combustion gases. Wear breathing apparatus with own air supply. Wear full protection depending on fire class. Use water spray to cool endangered containers. Dispose contaminated fire extinguishing water according to official directives.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures
Keep away from sources of ignition. No smoking. Arrange for sufficient air supply. Avoid eye and skin contact as well as inhalation. Keep away unnecessary people from the scene of an accident; ideally contrary to the wind direction. Danger of slipping.

6.2 Environmental precautions
Do not empty into drains. Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up
Absorb bigger quantities with fluid-binding material (e.g. universal binder, sand, diatomaceous earth, sawdust) and dispose of according to section 13.

6.4 Reference to other sections
Personal protective equipment see section 8. Waste disposal see section 13.

7. Handling and storage

7.1 Precautions for safe handling
Keep away from sources of ignition – No smoking Avoid inhaling the vapors. Ensure good ventilation. Take measures against electrostatic charge. Avoid eye and skin contact. Open and handle receptacle with care. Eating, drinking, smoking, as well as food-storage, is prohibited in workspace. Notes note on the packaging and current technical data sheet. Use working methods according to operating instructions.
Wash contaminated clothing before reuse. General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. Take off contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities
To avoid the unauthorized and children and kept in a safe place.
Do not store together with oxidizing and self-igniting products. Recommended storage temperature: < 25°C.
Protect the product against moisture.

7.3 Specific end uses
Primer - See technical data sheet and the product imprint.

8. Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

CAS No.: 79-20-9 EG No.: 201-185-2 Index No.: 607-021-00-X Reg. No. (REACH): -	**methyl acetate** CH: MAC: 100 ppm (310 mg/m^3)

CAS No.: 67-64-1 EG No.: 200-662-2 Index No.: 606-001-00-8 Reg. No. (REACH): 01-2119471330-49-XXXX	**aceton** CH: MAC: 500 ppm (1200 mg/m^3) CH: STEL: 1000 ppm (2400 mg/m^3) EU: TWA: 500 ppm (1210 mg/m^3) DE: TRHS urine: 50 mg/l (end of exposure or end of shift) [25/QS,1/3,4]

CAS No.: 141-78-6 EG No.: 205-500-4 Index No.: 607-022-00-5 Reg. No. (REACH): 01-2119475103-46-XXXX	**ethyl acetate** CH: MAC: 400 ppm (1400 mg/m^3) EU: TWA: 200 ppm (730 mg/m^3)

MAK = Maximum Workplace Concentration (TLV = Threshold Limit Value)
CH It's a swiss limit, edited by SUVA. If there is no limit from SUVA it's a work place limit (AGW) from Germany or another European state.

CAS No.: 67-64-1 EG No.: 200-662-2 Index No.: 606-001-00-8 Reg. No. (REACH): 01-2119471330-49-XXXX	**acetone** employee: DNEL: 186 mg/kg bw/day [dermal exposure route, long-term, systemic effects]; employee: DNEL: 2420 mg/m^3 [inhalative, short-term, local effects]; employee: DNEL: 1210 mg/m^3 [inhalative, long-term, systemic effects]; consumer: DNEL: 62 mg/kg bw/day [oral, long-term, systemic effects]; consumer: DNEL: 62 mg/kg bw/day [dermal exposure route, long-term, systemic effects]; consumer: DNEL: 200 mg/m^3 [inhalative, long-term, systemic effects]; environment: PNEC: 1.06 mg/l [sea water]; environment: PNEC: 10.6 mg/l [fresh water]; environment: PNEC: 30.4 mg/l [sediment, fresh water]; environment: PNEC: 3.04 mg/l [sediment, seawater]; environment: PNEC: 29.5 mg/l [soil]; environment: PNEC: 100 mg/l [microorganisms in wastewater treatment plants] [25/Q59/3]

CAS No.: 141-78-6 EG No.: 205-500-4 Index No.: 607-022-00-5 Reg. No. (REACH): 01-2119475103-46-XXXX	**ethyl acetate** employee: DNEL: 63 mg/kg [dermal exposure route, long-term, systemic effects]; employee: DNEL: 734 mg/m^3 [inhalative, long-term, systemic effects]; employee: DNEL: 734 mg/m^3 [inhalative, long-term, systemic effects]; employee: DNEL: 1468 mg/m^3 [inhalative, short-term, systemic effects]; employee: DNEL: 1468 mg/m^3 [inhalative, short-term, systemic effects]; consumer: DNEL: 4.5 mg/kg [oral, long-term, systemic effects]; consumer: DNEL: 37 mg/kg [dermal exposure route, long-term, systemic effects]; consumer: DNEL: 367 mg/m^3 [inhalative, long-term, systemic effects]; consumer: DNEL: 367 mg/m^3 [inhalative, long-term, local effects]; consumer: DNEL: 734 mg/m^3 [inhalative, short-term, systemic effects];

	consumer: DNEL: 734 mg/m^3 [inhalative, short-term, local effects]; environment: PNEC: 0.24 mg/l [fresh water]; environment: PNEC: 0.024 mg/l [sea water]; environment: PNEC: 1.65 mg/l [water, sporadic release]; environment: PNEC: 1.15 mg/kg [sediment, fresh water]; environment: PNEC: 0.115 mg/kg [sediment, seawater]; environment: PNEC: 0.24 mg/kg [soil]; environment: PNEC: 650 mg/l [microorganisms in wastewater treatment plants]; environment: PNEC: 200 mg/kg [oral, feed]; environment: PNEC: 0.148 mg/l [soil] [24/Q2/4]

8.2 Exposure controls

8.2.1 Appropriate engineering controls
Ensure good ventilation, e.g. by local suction, general exhaust air.
Comply with the workplace exposure limits.
If limits can't be adhered to, use appropriate respiratory protection.

8.2.2 Personal protective equipment

General data	Select personal protective equipment according to the CEN standards; discuss protective equipment with the supplier.
Eye/face protection	Tight-fitting protective goggles with side protection shield (EN 166).
Hand-/Body protection	Use chemical-resistant protective gloves according to EN 374.
Protective clothing	Wear solvent-resistant protective clothing according to EN ISO 20345.
Respiratory protection	In case of insufficient ventilation or if limit values cannot be complied, use air respirator. Filters type AXBEK in accordance with EN 14387. Follow the wear time limits for breathing apparatus.
Hygiene measures	Do not eat, drink or smoke while at work. Wash hands before breaks and after work.
Thermal hazards	Not applicable.



On the basis of the contents and our experience the following non-binding recommendations for the selection of the material of the protective gloves (minimum layer thickness: 0.4 mm):

Recommended glove material:	Butyl rubber (Butyl)
Inappropriate glove material:	Textile Materials

The selection of suitable depends upon the material, and also upon the quality of the gloves. The degree of protection will vary from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the materials used for gloves cannot be predetermined; it is therefore necessary to check this before using the product.
The manufacturer's information on permeability and breakthrough times of the protective gloves must be observed and followed.

8.2.3 Environmental exposure controls
More information that is detailed is not available yet.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	transparent (opaque)
Density	0.82 g/cm3 20°C
Viscosity	40 mPas 20°C
Odour	Characteristic

Odour threshold	Not determined
pH-level	Not determined
Melting point/freezing point	Not determined
Initial boiling point/boiling range	Not determined
Decomposition temperature	Not determined
Rate of evaporation	Not determined
Flashpoint	-18°C
Auto-ignition temperature	Not determined
Lower explosive limits	2.1 Vol%
Upper explosive limits	16 Vol%
Vapour pressure	247 hPa 20°C
Vapour density (Air = 1)	Not determined
Explosive properties	The product is not explosive. In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	Not determined

9.2 Other information

Solubility in / Miscibility with water.	Partially miscible in water
Solubility in / Miscibility in	Not determined
Partition coefficient n-Octanol/Water	Not determined
Conductivity	Not determined
VOC-content (EU)	88.3%
VOC-content (CH)	88.3%

10. Stability and reactivity

10.1 Reactivity
The product has not been tested.

10.2 Chemical stability
The product is stable when properly stored and handled.

10.3 Possibility of hazardous reactions
No effects are known if used as intended.

10.4 Conditions to avoid
Heating, open flame, ignition sources.

10.5 Incompatible materials
None known.

10.6 Hazardous decomposition products
No decomposition if used according to specifications.
In case of fire or extreme heat, see section 5.2.

11. Toxicological information

11.1 Information on toxicological effects
-

11.2. Toxicological information of hazardous ingredients

CAS No.: 79-20-9 EG No.: 201-185-2 Index No.: 607-021-00-X Reg. No. (REACH): -	**methyl acetate** acute toxicity: LD50: >5000 mg/kg [oral, rat]; acute toxicity: LD50: >2000 mg/kg [dermal exposure route, rat]; corrosive/irritant effect on the skin: frequent and prolonged skin contact may cause irritation; symptoms: skin and mucous membrane irritation possible. Inhalation of high vapor concentrations may lead to central nervous system depression and narcosis.

CAS No.: 67-64-1 EG No.: 200-662-2	**acetone** acute toxicity: LD50: 5800 mg/kg [oral, rat, OECD 401];

Index No.: 606-001-00-8 Reg. No. (REACH): 01-2119471330-49	acute toxicity: LD50: 3000 mg/kg [oral, mouse]; acute toxicity: LD50: 6665 mg/kg [oral]; acute toxicity: LD50: >15800 mg/kg [dermal exposure route, rat]; acute toxicity: LC50: 76 mg/l/4h [inhalative, rat, vapours]; corrosive/irritant effect on the skin: non-irritant, wiederholter Kontakt kann zu spröder oder rissiger Haut führen [Guinea pig]; serious eye damage/irritation: irritant [rabbit, OECD 405, Eye Irrit. 2]; respiratory/skin sensitization: not sensitising [Guinea pig, OECD 406]; germ cell mutagenicity: negative [mouse, OECD 476 (In Vitro Mammalian Cell Gene Mutation Test]; germ cell mutagenicity: negative [Salmonela typhimurium, OEDC 471 (Bacterial Reverse Mutation Test)]; germ cell mutagenicity: negative [mammals, OECD 473 (In Vitro Mammalian Chromosome Aberration Test)]; symptoms: unconsciousness, vomiting, headaches, gastrointestinal complaints, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness, drowsiness. specific target organ toxicity - repeated exposure (STOT RE): NOAEL, 900 mg/kg bw/d [oral, rat, OECD (Repeated Dose 90-Day Oral Toxicity Study in Rodents)] [24/Q2/2]

CAS No.: 141-78-6 EG No.: 205-500-4 Index No.: 607-022-00-5 Reg. No. (REACH): 01-2119475103-46-XXXX	**ethyl acetate** acute toxicity: LD50: 4934 mg/kg [oral, OECD 401, rabbit]; acute toxicity: LD50: >20000 mg/kg [dermal exposure route, rabbit]; acute toxicity: LC0: >29.3 mg/l/4h [inhalative, rat, vapours]; corrosive/irritant effect on the skin: non-irritant, wiederholter Kontakt kann zu spröder oder rissiger Haut führen [rabbit, OECD 404]; serious eye damage/irritation: irritant [rabbit, OECD 405, Eye Irrit. 2]; respiratory/skin sensitization: not sensitising (skin contact) [Guinea pig, OECD 406]; germ cell mutagenicity: negative [Salmonella typhimurium OECD 471]; germ cell mutagenicity: negative [mammals, OECD 473]; germ cell mutagenicity: negative [mammals, OECD 474]; carcinogenicity: negative; reproductive toxicity: negative; aspiration hazard: no; specific target organ toxicity - single exposure (STOT SE): [3, H336, may cause: drowsiness, drowsiness]; specific target organ toxicity - repeated exposure (STOT RE): [NOAEL, inhalative, 0.002 mg/kg/90d, rat]; specific target organ toxicity - repeated exposure (STOT RE): [NOAEL, oral, 900 mg/kg/90d, rat]; symptoms: loss of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, corneal opacity, cough, headaches, gastrointestinal complaints, intoxication, drowsiness, mucous membrane irritation, dizziness, salivary flow, nausea and vomiting [24/Q2/4]

12. Ecological information

12.1 Toxicity
The product is not classified as dangerous for the environment.
Aquatic toxicity Germany (Self-classification): WGK 1 Slightly hazardous to water

12.2 Persistence and degradability
No information is available.

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water	

12.4 Mobility in soil
No information is available.

12.5 Results of PBT and vPvB assessment
See section 2.3.

12.6 Other adverse effects
Do not allow product to reach ground water, water course or sewag system.

12.7 Additional ecotoxicological information

CAS No.: 79-20-9 EG No.: 201-185-2 Index No.: 607-021-00-X Reg. No. (REACH): -	**methyl acetate** acute toxicity, fish: LC50: 250-350 mg/l/96h [Brachydanio rerio]; acute toxicity, daphnia: EC50: 1027 mg/l/48h [Daphnia] acute bacteriotoxicity: EC50: 6100 mg/l/30min [Photobacterium phosphoreum]; persistence and degradability: [CSB 1510 mg/g; easily biodegradable]; other information: Do not allow to reach ground water, water course or sewage system.

CAS No.: 141-78-6 EG No.: 205-500-4 Index No.: 607-022-00-5 Reg. No. (REACH): 01-2119475103-46-XXXX	**ethyl acetate** acute toxicity, fish: NOEC/NOEL: 9.6 mg/l/32d [Pimephales promelas]; acute toxicity, fish: LC50: 230 mg/l/96h [Pimephales promelas]; acute toxicity, fish: LC50: 333 mg/l/48h [Leuciscusidus]; acute toxicity, daphnia: EC50: 610 mg/l/48h [Daphnia magna]; acute toxicity, daphnia: NOEC/NOEL: 2.4 mg/l/21d [OECD 211, Daphnia magna]; acute toxicity, daphnia: EC50: 165 mg/l/48h [Daphnia cucullata]; acute toxicity, algae: EC50: 5600 mg/l/48h [Desmodesmus subspicatus]; acute toxicity, algae: EC50: >2000 mg/l/96h [OECD 201, Pseudokirch neriella subcapitata]; acute toxicity, algae: NOEC/NOEL: 2000mg/l /96h [OECD 201, Scenedesmus subspicatus]; acute toxicity, algae: NOEC/NOEL: >100 mg/l/72h [OECD 201, Desmodesmus Subspicatus]; acute toxicity, algae: EC50: 3300 mg/l/48h [Scenedesmus subspicatus]; persistence and degradability: 79%/20d [OECD301 D, easily biodegradable]; bioaccumulative potential: BCF: 30/72h [fish]; bioaccumulative potential: Log Kow, 0.68 [OECD107, is not to be expected, (LogPow <1), 25 °C] mobility in soil: [H (Henry), 0.00012 atm* m3/mol]; mobility in soil: Koc 3; results of PBT and vPvB assessment: no PBT substance, no vPvB substance; acute bacteriotoxicity: EC10: 2900 mg/l/16h [Escherichia coli]; acute bacteriotoxicity: EC50: 5870 mg/l15 min [Photobaterium phosphoreum]; acute bacteriotoxicity: EC10: 2900 mg/l/18h [Pseudomonas putida] [24/Q2/4]

CAS No.: 67-64-1 EG No.: 200-662-2 Index No.: 606-001-00-8 Reg. No. (REACH): 01-2119471330-49-XXXX	**acetone** acute toxicity, fish: LC50: 5540 mg/l/96h [Oncorhynchus mykiss]; acute toxicity, fish: LC50: 7500 mg/l/96h [Leuciscus idus]; acute toxicity, fish: LC50: 5540-8300 mg/l/96h [Lepomis macrochirus]; acute toxicity, daphnia: EC50: 6100-12700 mg/l/48h [Daphnia magna]; acute toxicity, algae: IC50: 7500 mg/l/8d [Scendesmus quadricauda]; acute toxicity, algae: EC50: 7500 mg/l/96h [Selenastrum capricornutum]; acute toxicity, algae: NOEC/NOEL: 3400 mg/l/48h [Pseudokirchnerie lla subcapitata]; persistence and degradability: easily biodegradable [91%/28d, OECD 301 B]; bioaccumulative potential: non-bioaccumulative [partition coefficient: Log Pow: -0.24, BCF: 0.19]; acute bacteriotoxicity: EC5:1700 mg/l/16h[Pseudomonas putida]; acute bacteriotoxicity: EC5: 530 mg/l/8d [Microcystis aeruginosa]; other information: [BOD5, 1900 mg/g; COD, 2100 mg/g]

13. Disposal considerations

13.1 Waste treatment methods

Waste disposal according to official state regulations.

Waste treatment options:
08 00 00 – Wastes from the manufacture, formulation, supply and use (MFSU) of coatings (paints, varnishes and vitreous enamels), adhesives, sealants and printing inks
08 04 09 – Waste adhesives and sealants containing organic solvents or other dangerous substances.

Contaminated packages: Disposal must be made according to official regulations. If possible empty packaging completely. Packagings that cannot be cleaned are to be disposed off in the same manner as the product. Uncontaminated and cleaned packaging can be recycled. Uncleaned container do not perforate, cut up or weld. Residues may cause an explosion hazard. 15 01 01 – paper and cardboard packaging. 15 01 04 – metallic packaging.
The waste code numbers mentioned are recommendations based on the probable use of the product. The particular application and local disposal situation obtaining for the user may lead to other waste codes being assigned as well.

14. Transport information

14.1 UN-Number:
ADR, RID, ADN, IMDG, IATA: **UN 1866**

14.2 UN proper shipping name
ADR, RID: UN 1866 RESIN SOLUTION
IMDG, IATA: HYDROCARBONS, LIQUID, N.O.S (Resin solution)

14.3 Transport hazard class(es):

ADR, RID, ADN, IMDG, IATA: 3

Flammable liquids
Flammable liquids



14.4 Packing group:
ADR, RID, ADN, IMDG, IATA: III

14.5 Enviromental hazards:

Dangerous to the environment: No
Marine pollutant: No

14.6 Special precautions for user:

Kemmler number:	n.a.
EMS number:	F-E, S-D

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable, because of general cargo and not bulk cargo.

14.8 Additional information:

ADR / RID: LQ – Limited Quantities:	6 L
ADR / RID: Tunnel restriction code:	D/E
UN “Model Regulation”:	UN1866, Resin solution, liquid, 3, III

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substances or mixture

Classification and labelling see section 2.
Classification of the preparation has been done by calculation or based on studies/test on the product itself or experience with similar mixtures.

Further national and further regulations, limitations and legal requirements

VOC content according to swiss VOC regulation (VOCV) see section 9.2.
Water hazard class (WGK) see section 12.1.
Observe employment restrictions for young people (CH: SR 822.115).
Chemicals regulation (ChemV), ordinance on chemicals risk reduction (ChemRRV), Luftreinhalte-Verordnung (LRV), Ordinance on protection against major accidents (StFV), professional association principles/industrial medicine regulations

15.2 Chemical Safety Assessment
A chemical safety assessment is not provided for mixtures.

16. Other information

Hazards used in the document (H-phrases):

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Other recommended sources for more information:
- Federal Office of Public Health (Switzerland): www.bag.admin.ch (German/French/Italian/English)

List of relevant abbreviations that may be used in the document:

Abbreviation	Full text / Meaning
ADR	Accord européen realtif au transport international des marchandises Dangereuses par Route (= European agreement concerning the international carriage of dangerouse goods by road)
AGW, Spb.-Üf.	AGW = Arbeitsplatzgrenzwert (occupational limit value), Spb.-Üf. = Spitzenbegrenzung (peak limit) – Überschreitungsfaktor (exceedance factor) (1 bis 8) and category (I, II) for short-term values (TRGS 900, germany)
AOEL	Acceptable Operator Exposure Level
Aquatic Acute	Hazardous to the aquatic environment - Acute
Aquatic Chronic	Hazardous to the aquatic environment – Chronic
Asp. Tox.	Aspiration hazard (Danger when inhaling)
ATE	Acute Toxicity Estimates
BAG	Office for health (Bundesamt für Gesundheit, Schweiz)
BAT	Biological tolerance values at the workplace (Biologische Arbeitsstofftoleranzwerte, Schweiz)
BG	Trade association (Berufsgenossenschaft)
BGR	Trade association regulations (Berufsgenossenschaftliche Regeln)
BGV	Trade association regulations (Berufsgenossenschaftliche Vorschrift)
Carz.	Carcinogenic substance
CAS-Nr.	Chemical Abstracts Service
CH	Swiss confederation (from the latin Confoederatio Helvetica)
CH: MAK:	Swiss limit of maximum allowable concentration, issued by the swiss accident insurance fund. (Schweizerischen Unfallversicherungsanstalt (SUVA)
CLP	Classification, Labelling and Packaing (REGULATION (EG) Nr. 1272/2008)
CPID	Chemical Product IDentification.
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
EG-Nr.	Substances of the EC material inventory, consisting of 7 digits (Syntax: XXX-XXX-X). Comprises waste materials (EINECS), new substances (ELINCS) as well as the No-Longer-Polymers-Liste (NLP-Liste).
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Irrit.	Eye irritant, depending on the category Eye irritation possible to serious eye damage.
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IATA	International Air Transport Association
IMDG-Code	International Maritime Code for Dangerous Goods
Index-Nr.	Indexation of dangerous substances of appendix 5 in the VO(EG)1272/2008 (or annex I of directive 67/548/EWG) with the following syntax: XXX-XXX-XX-X
LC	Lethal concentration
LD	Lethal (fatal) dose
LD50	Lethal dose, 50%
Met. Corr.	On metal corrosive acting substance or mixture
Muta.	Substance with germ cell mutagenicity
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
Ozone	Hazardous for the ozone layer
PBT	Persistent, bioaccumulative, and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (Verordnung (EG) Nr. 1907/2006 zur Registrierung, Bewertung, Zulassung und Beschränkung chemischer Stoffe)
Repr.	Reproductive toxicity
Resp. Sens.	Sensitising for respiratory tract
SCL	Specific concentration limits
Skin Irrit.	Skin irritant – corrosive/irritant to skin
Skin Sens.	Sensitising for the skin
STOT RE	Specific target organ toxicity – repeated exposure
STOT SE	Specific target organ toxicity – single exposure
TRGS	Technical rules on hazardous substances

VOC	Volatile organic compounds
VOCV	VOC-regulation (Swiss)
vPvB	Very persistent and very bioaccumulative

Department issuing data specification sheet: See section 1.3.
This safety data sheet replaces all previous versions.

Disclaimer: The specifications rest on the today's stand of our knowledge. It does not constitute a legally binding assurance of specific product properties.

© **Wisabax AG** - Any publication/modification requires written approval from Wisabax AG. Created with the help of SDS (Safety Data Sheets), an in-house software solution designed to simplify the creation of multilingual SDS.