

Wisaclean® color

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade Name	Wisaclean color
Item number	PR 331.500
BAG-Register number (CH)	CPID: 122195-76

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Detergents
Uses advised against	All applications that are not explained in this technical data sheet.
Field for application [SU]	SU21 – Consumer use: Private households (= community = consumer) SU22 – Commercial use: Public domain (administration, education, entertainment, services, trade)

1.3 Details of the supplier of the safety data sheet

Supplier	Wisabax AG Kleb- und Dichtstoffe	
Address	Grossmatte 21 / Postfach CH-6014 Luzern-Littau	
Phone	+41 (0)41 250 18 18	
Email	info@wisabax.ch	
URL	www.wisabax.ch	
Information contact	Technical Dept. - Mr B. Wicki Environment Dept. - Mrs E. Svets	

1.4 Emergency telephone number

24h emergency number (just possible in switzerland)	Tel. 145	
Tox Info Suisse (ancient swiss toxicological informations centre) For emergencies from all the countries 24h accessible in german, french, italian oder english. For not urgent cases see www.toxinfo.ch .	Tel. +41 (0)44 251 51 51	

2. Hazards identification

2.1 Classification of the substance or mixture according to (EC) Nr. 1272/2008 (CLP).

-

2.2 Labelling according to Regulation (EC) Nr. 1272/2008 (CLP)

EUH210 Safety data sheet available on request.

2.3 Other hazards

Persons suffering from allergic reactions to this product should avoid contact with de product.

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

3. Composition/information on ingredients

3.1 Substances

This product is a mixture, for more see section 3.2.

3.2 Description of the mixture

Wisaclean® color

Mixture of the substances listed below with harmless additions.

Content: 1 % - 10 %

CAS No.: 64-17-5 EG No.: 200-578-6 Index No.: 603-002-00-5 Reg. No. (REACH): 01-2119457610-43-XXXX	ethanol	Flam. Liq. 2, H225; Eye Irrit. 2, H319
---	---------	---

Note: H-phrases and abbreviations are detailed in section 16.

4. First aid measures

4.1 Description of first aid measures

General information	Observe the general rules of first aid measures. Refresh occasionally your knowledge. If medical advice is required, have this safety data sheet, the packaging or the label ready.
Following inhalation	Supply fresh air. Loosen restrictive clothing. Place in a resting position. Consult a doctor depending on the symptoms.
Following skin contact	Remove contaminated clothing immediately. Wash skin with much water and soap. Consult a doctor depending on the symptoms, if possible, show this container or label.
Following eye contact	Remove contact lenses, if possible. Rinse thoroughly with water and consult a doctor. Present this safety data sheet or product label.
Following ingestion	Rinse mouth thoroughly with water. Keep airways free. Telephone the emergency number or consult a doctor. If it is possible, present this safety data sheet or product label.

4.2 Most important symptoms and effects, both acute and delayed

In certain cases, symptoms of intoxication may only appear after a longer period of time/after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

-

5. Firefighting measures

5.1 Extinguishing media

Always adapt firefighting measures to the surroundings and the size of the fire.

Suitable extinguishing media: Water spray jet, Dry powder fire extinguishers, Alcohol-resistant foam, Carbon dioxide
Unsuitable extinguishing media: none known

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire:
Carbon oxide, Nitrogen oxide (NOx), Sulphur oxides, Toxic gases.

5.3 Advice for fire-fighters

Do not inhale combustion gases. Wear breathing apparatus with own air supply. Wear full protection depending on fire class. Use water spray to cool endangered containers. Dispose contaminated fire extinguishing water according to official directives.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid eye and skin contact as well as inhalation. Keep away unnecessary people from the scene of an accident; ideally contrary to the wind direction. Danger of slipping.

6.2 Environmental precautions

Dam up larger quantities. Do not empty into drains. Prevent surface and ground-water infiltration, as well as ground penetration. Eliminating a leak, if this can be done safely. When accidental discharge into channelization has happened, inform the corresponding officials.

Wisaclean® color

6.3 Methods and material for containment and cleaning up

Absorb bigger quantities with fluid-binding material (e.g. universal binder, sand, diatomaceous earth, sawdust) and dispose of according to section 13.

6.4 Reference to other sections

Personal protective equipment see section 8. Waste disposal see section 13.

7. Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation. Keep away from sources of ignition – No smoking Avoid eye and skin contact. Eating, drinking, smoking, as well as food-storage, is prohibited in workspace. Notes note on the packaging and current technical data sheet. Use working methods according to operating instructions. Wash contaminated clothing before reuse. General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. Take off contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

To avoid the unauthorized and children and kept in a safe place. Do not store warnings in corridors and stairwells. Store only in original container and keep locked up. Store in a dry place. Store in a frost-free place. Store at room temperature.

7.3 Specific end uses

Detergents - See technical data sheet and the product imprint.

8. Exposure controls/personal protection

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

CAS No.: 64-17-5 EG No.: 200-578-6 Index No.: 603-002-00-5 Reg. No. (REACH): 01-2119457610-43-XXXX	ethanol CH: MAC: 500 ppm (960 mg/m ³) CH: STEL: 1000 ppm (1920 mg/m ³)
---	---

MAK = Maximum Workplace Concentration (TLV = Threshold Limit Value)

CH It's a swiss limit, edited by SUVA. If there is no limit from SUVA it's a work place limit (AGW) from Germany or another European state.

CAS No.: 64-17-5 EG No.: 200-578-6 Index No.: 603-002-00-5 Reg. No. (REACH): 01-2119457610-43-XXXX	ethanol employee: DNEL: 1900 mg/m ³ [inhalative, short-term, local effects]; employee: DNEL: 950 mg/m ³ [inhalative, long-term, systemic effects]; employee: DNEL: 343 mg/kg bw/d [dermal exposure route, long-term, systemic effects]; consumer: DNEL: 950 mg/m ³ [inhalative, short-term, local effects]; consumer: DNEL: 950 mg/m ³ [dermal exposure route, long-term, systemic effects]; consumer: DNEL: 114 mg/m ³ [inhalative, long-term, systemic effects]; consumer: DNEL: 87 mg/kg [oral, long-term, systemic effects]; consumer: DNEL: 206 mg/kg bw/d [dermal exposure route, long-term, systemic effects]; environment: PNEC: 0.96 mg/l [fresh water]; environment: PNEC: 0.79 mg/l [sea water]; environment: PNEC: 2.75 mg/l [water, sporadic release]; environment: PNEC: 580 mg/l [microorganisms in wastewater treatment plants]; environment: PNEC: 3.6 mg/kg dw [sediment, fresh water]; environment: PNEC: 0.63 mg/kg dw [soil]; environment: PNEC: 0.72 mg/kg feed [oral, feed]; environment: PNEC: 2.9 mg/kg dw [sediment, seawater]
---	--

Wisaclean® color

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Comply with the workplace exposure limits.

If limits can't be adhered to, use appropriate respiratory protection.

8.2.2 Personal protective equipment

General data	Select personal protective equipment according to the CEN standards; discuss protective equipment with the supplier.
Eye/face protection	Tight-fitting protective goggles with side protection shield (EN 166).
Hand-/Body protection	Use chemical-resistant protective gloves according to EN 374.
Protective clothing	Wear suitable protective clothing, e.g long-sleeved clothes and safety shoes according to EN ISO 20345.
Respiratory protection	In case of insufficient ventilation or if limit values cannot be complied, use air respirator. Filters type AXBEK in accordance with EN 14387.
Hygiene measures	Do not eat, drink or smoke while at work. Wash hands before breaks and after work.
Thermal hazards	Not applicable.



On the basis of the contents and our experience the following non-binding recommendations for the selection of the material of the protective gloves (minimum layer thickness: 0.4 mm):

Recommended glove material:	Butyl rubber (Butyl), Nitrile rubber/Nitrile latex (NBR), Polychloroprene (CR)
Inappropriate glove material:	Textile Materials

The selection of suitable depends upon the material, and also upon the quality of the gloves. The degree of protection will vary from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the materials used for gloves cannot be predetermined; it is therefore necessary to check this before using the product.

The manufacturer's information on permeability and breakthrough times of the protective gloves must be observed and followed.

8.2.3 Environmental exposure controls

More information that is detailed is not available yet.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	yellow
Density	~0.99 g/cm ³ (20 °C)
Viscosity	Not determined
Odour	lemon
Odour threshold	Not determined
pH-level	~7
Melting point/freezing point	Not determined
Initial boiling point/boiling range	Not determined
Decomposition temperature	Not determined
Rate of evaporation	Not determined
Flashpoint	53 °C
Auto-ignition temperature	Not determined
Lower explosive limits	Not determined
Upper explosive limits	Not determined
Vapour pressure	Not determined
Vapour density (Air = 1)	Not determined
Explosive properties	The product is not explosive. In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	No

Wisaclean® color

9.2 Other information

Solubility in / Miscibility with water.	Well miscible with water
Solubility in / Miscibility in	Not determined
Partition coefficient n-Octanol/Water	Not determined
Conductivity	Not determined
VOC-content (EU)	76.8 g/l ~10 Vol. %
VOC-content (CH)	76.8 g/l ~10 Vol. %

10. Stability and reactivity

10.1 Reactivity

The product is not reactive under normal conditions.

10.2 Chemical stability

The product is stable when properly stored and handled.

10.3 Possibility of hazardous reactions

No effects are known if used as intended.

10.4 Conditions to avoid

No effects are known if used as intended.

10.5 Incompatible materials

Oxidizer

10.6 Hazardous decomposition products

No decomposition if used according to specifications. In case of fire or extreme heat, see section 5.2.

11. Toxicological information

11.1 Information on toxicological effects

-

11.2. Toxicological information of hazardous ingredients

CAS No.: 64-17-5
EG No.: 200-578-6
Index No.: 603-002-00-5
Reg. No. (REACH): 01-2119457610-43-XXXX

ethanol

acute toxicity: LD50: 10470 mg/kg [oral, rat, OECD 401];
acute toxicity: LD50: >2000 mg/kg [dermal exposure route, rabbit, OECD 402];
acute toxicity: LC50: 117-125 mg/l/4h [inhalative, rat, OECD 402];
corrosive/irritant effect on the skin: non-irritant [rabbit, OECD 404];
serious eye damage/irritation: slightly irritant [rabbit, OECD 405];
respiratory/skin sensitization: not sensitising [mouse, OECD 429,];
germ cell mutagenicity: [salmonella typhimurium, OECD 471, negative; OECD 475, negative; mouse, OECD 476, negative; OECD 473, negative; OECD 471, negative];
carcinogenicity: NOAEL: >3000 mg/kg [rat, OECD451, 24 months];
reproductive toxicity: NOAEL: 5200 mg/kg/bw/d [rat];
specific target organ toxicity - repeated exposure (STOT RE): NOAL >20 mg/l [rat, OECD 403, males];
specific target organ toxicity - repeated exposure (STOT RE): NOAEL: 1730 mg/kg/d [rat, OECD 408, female];
symptoms: shortness of breath, drowsiness, unconsciousness, drop in blood pressure, vomiting, cough, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea;
experience on humans: Excessive alcohol consumption during pregnancy induces fetal alcohol syndrome (reduced birth weight, physical and mental disorders). There is no indication that this syndrome is also caused by dermal or inhalative absorption.

Wisaclean® color

12. Ecological information

12.1 Toxicity

The product is not classified as dangerous for the environment.
Aquatic toxicity Germany (Self-classification): WGK 1 Slightly hazardous to water

12.2 Persistence and degradability

No information is available.

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water	
---------------------------------------	--

12.4 Mobility in soil

No information is available.

12.5 Results of PBT and vPvB assessment

See section 2.3.

12.6 Other adverse effects

Do not allow product to reach ground water, water course or sewage system.

12.7 Additional ecotoxicological information

CAS No.: 64-17-5 EG No.: 200-578-6 Index No.: 603-002-00-5 Reg. No. (REACH): 01-2119457610-43-XXXX	ethanol acute toxicity, fish: LC50: 13000 mg/l/96h [Oncorhynchus mykiss, OECD 203]; acute toxicity, daphnia: LC50: 12340 mg/l/48h [Daphnia magna]; acute toxicity, algae: EC50: 12900 mg/l/48h [Selenastrum capricornutum, OECD 201]; acute toxicity, algae: EC50: 275 mg/l/72h [Chlorella vulgaris, OECD 201]; persistence and degradability: 97%, easily biodegradable [OECD 301B]; bioaccumulative potential: -0.35, 24 °C [Log KOW], 0.6211 [BSB5/CSB]; mobility in soil: [H (Henry), 0,000138]; other information: [BOD5, 1 g/g; COD, 1.9 g/g]; water solubility: miscible [24/Q1/4]
---	---

13. Disposal considerations

13.1 Waste treatment methods

Waste disposal according to official state regulations.

Waste treatment options: 20 01 30 – Detergent with exceptions of those who fall under the 20 01 29
Contaminated packages: Disposal must be made according to official regulations. If possible empty packaging completely. Packagings that cannot be cleaned are to be disposed off in the same manner as the product. Uncontaminated and cleaned packaging can be recycled.
The waste code numbers mentioned are recommendations based on the probable use of the product. The particular application and local disposal situation obtaining for the user may lead to other waste codes being assigned as well.

14. Transport information

14.1 UN-Number:

ADR, RID, ADN, IMDG, IATA: Not applicable

14.2 UN proper shipping name

ADR, RID, ADN, IMDG, IATA: Not applicable

14.3 Transport hazard class(es):

ADR, RID, ADN, IMDG, IATA: Not applicable	
---	--

Wisaclean® color

14.4 Packing group:

ADR, RID, ADN, IMDG, IATA: Not applicable

14.5 Environmental hazards:

Dangerous to the environment: No

Marine pollutant: No

14.6 Special precautions for user:

Kemmler number:	Not applicable
EMS number:	Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Inapplicable

14.8 Additional information:

ADR: LQ – Limited Quantities:	Not applicable
ADR: Transport category:	Not applicable
ADR: Tunnel restriction code:	Not applicable
UN "Model Regulation":	Inapplicable

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substances or mixture

Classification and labelling see section 2.

Classification of the preparation has been done by calculation or based on studies/test on the product itself or experience with similar mixtures.

Further national and further regulations, limitations and legal requirements

VOC content according to swiss VOC regulation (VOCV) see section 9.2.
Water hazard class (WGK) see section 12.1.
Observe employment restrictions for young people (CH: SR 822.115).
Chemicals regulation (ChemV), ordinance on chemicals risk reduction (ChemRRV), Luftreinhalte-Verordnung (LRV), Ordinance on protection against major accidents (StFV), professional association principles/industrial medicine regulations

15.2 Chemical Safety Assessment

A chemical safety assessment is not provided for mixtures.

16. Other information

Hazards used in the document (H-phrases):

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

Other recommended sources for more information:

 - Federal Office of Public Health (Switzerland): www.bag.admin.ch (German/French/Italian/English)

List of relevant abbreviations that may be used in the document:

Abbreviation	Full text / Meaning
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route (= European agreement concerning the international carriage of dangerous goods by road)
AGW, Spb.-Üf.	AGW = Arbeitsplatzgrenzwert (occupational limit value), Spb.-Üf. = Spitzenbegrenzung (peak limit) – Überschreitungsfaktor (exceedance factor) (1 bis 8) and category (I, II) for short-term values (TRGS 900, Germany)
AOEL	Acceptable Operator Exposure Level
Aquatic Acute	Hazardous to the aquatic environment - Acute
Aquatic Chronic	Hazardous to the aquatic environment – Chronic
Asp. Tox.	Aspiration hazard (Danger when inhaling)
ATE	Acute Toxicity Estimates
BAG	Office for health (Bundesamt für Gesundheit, Schweiz)
BAT	Biological tolerance values at the workplace (Biologische Arbeitsstofftoleranzwerte, Schweiz)
BG	Trade association (Berufsgenossenschaft)
BGR	Trade association regulations (Berufsgenossenschaftliche Regeln)
BGV	Trade association regulations (Berufsgenossenschaftliche Vorschrift)
Carz.	Carcinogenic substance
CAS-Nr.	Chemical Abstracts Service

Wisaclean® color

CH	Swiss confederation (from the latin Confoederatio Helvetica)
CH: MAK:	Swiss limit of maximum allowable concentration, issued by the swiss accident insurance fund. (Schweizerischen Unfallversicherungsanstalt (SUVA))
CLP	Classification, Labelling and Packaing (REGULATION (EG) Nr. 1272/2008)
CPID	Chemical Product IDentification.
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
EG-Nr.	Substances of the EC material inventory, consisting of 7 digits (Syntax: XXX-XXX-X). Comprises waste materials (EINECS), new substances (ELINCS) as well as the No-Longer-Polymers-Liste (NLP-Liste).
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Irrit.	Eye irritant, depending on the category Eye irritation possible to serious eye damage.
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IATA	International Air Transport Association
IMDG-Code	International Maritime Code for Dangerous Goods
Index-Nr.	Indexation of dangerous substances of appendix 5 in the VO(EG)1272/2008 (or annex I of directive 67/548/EWG) with the following syntax: XXX-XXX-XX-X
LC	Lethal concentration
LD	Lethal (fatal) dose
LD50	Lethal dose, 50%
Met. Corr.	On metal corrosive acting substance or mixture
Muta.	Substance with germ cell mutagenicity
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
Ozone	Hazardous for the ozone layer
PBT	Persistent, bioaccumulative, and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (Verordnung (EG) Nr. 1907/2006 zur Registrierung, Bewertung, Zulassung und Beschränkung chemischer Stoffe)
Repr.	Reproductive toxicity
Resp. Sens.	Sensitising for respiratory tract
SCL	Specific concentration limits
Skin Irrit.	Skin irritant – corrosive/irritant to skin
Skin Sens.	Sensitising for the skin
STOT RE	Specific target organ toxicity – repeated exposure
STOT SE	Specific target organ toxicity – single exposure
TRGS	Technical rules on hazardous substances
VOC	Volatile organic compounds
VOCV	VOC-regulation (Swiss)
vPvB	Very persistent and very bioaccumulative

Department issuing data specification sheet: See section 1.3.

This safety data sheet replaces all previous versions.

Disclaimer: The specifications rest on the today's stand of our knowledge. It does not constitute a legally binding assurance of specific product properties.

© **Wisabax AG** - Any publication/modification requires written approval from Wisabax AG. Created with the help of SDS (Safety Data Sheets), an in-house software solution designed to simplify the creation of multilingual SDS.