

# Wisapur<sup>®</sup>-duo 912 Härter

## 1. Identification of the substance/mixture and of the company/undertaking


### 1.1 Product identifier

Trade Name	<b>Wisapur-duo 912 Hardener (Component B)</b>
Note: Two-component product	Please also refer to the safety data sheet of the other component.
Item number	PU 82.912
BAG-Register number (CH)	CPID: 327533-12 UFI: 3A80-E0N0-J00U-7XH6


### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Adhesive
Uses advised against	All applications that are not explained in this technical data sheet.
Field for application [SU]	SU22 – Commercial use: Public domain (administration, education, entertainment, services, trade)

### 1.3 Details of the supplier of the safety data sheet

Supplier	<b>Wisabax AG</b> Kleb- und Dichtstoffe	
Address	Grossmatte 21 / Postfach CH-6014 Luzern-Littau	
Phone	+41 (0)41 250 18 18	
Email	info@wisabax.ch	
URL	www.wisabax.ch	
Information contact	Technical Dept. - Mr B. Wicki Environment Dept. - Mrs E. Svets	

### 1.4 Emergency telephone number

<b>24h emergency number</b> (just possible in switzerland)	<b>Tel. 145</b>	
<b>Tox Info Suisse</b> (ancient swiss toxicological informations centre) <b>For emergencies from all the countries</b> 24h accessible in german, french, italian oder english. For not urgent cases see www.toxinfo.ch.	<b>Tel. +41 (0)44 251 51 51</b>	



## 2. Hazards identification

### 2.1 Classification of the substance or mixture according to (EC) Nr. 1272/2008 (CLP).

Hazard class	Hazard category	Hazard warnings
Eye Irrit.	2	H319 Causes serious eye irritation.
STOT SE	3	H335 May cause respiratory irritation.
Skin Irrit.	2	H315 Causes skin irritation.
Resp. Sens.	1	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317 May cause an allergic skin reaction.
Carc.	2	H351 May probably cause cancer.
STOT RE	2	H373 May cause damage to organs through prolonged or repeated exposure through inhalation (airways).

# Wisapur<sup>®</sup>-duo 912 Härter

## 2.2 Labelling according to Regulation (EC) Nr. 1272/2008 (CLP)

Pictograms(e)	 
Signal word(s)	<b>Danger</b>
Hazard warning(s) [H-statements]	<p>H319 Causes serious eye irritation.                      H335 May cause respiratory irritation.                      H315 Causes skin irritation.                      H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.                      H317 May cause an allergic skin reaction.                      H351 May probably cause cancer.                      H373 May cause damage to organs through prolonged or repeated exposure through inhalation (airways).</p>
Safety instruction(s) [P-statements]	<p>P201 Obtain special instructions before use.                      P260 Do not breathe vapour / aerosol.                      P280 Wear protective gloves/protective clothing/eye protection/face protection.                      P284 [In case of inadequate ventilation] wear respiratory protection.                      P 302 + P352 IF ON SKIN: Wash with plenty of water/...                      P304 + P340 IF INHALED: IF INHALED: Remove person to fresh air and keep comfortable for breathing.                      P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.                      P308 + P313 IF exposed or concerned: Get medical advice/attention.</p>
Special marking(s) [EUH-Phrases]	<p>EUH204 Contains isocyanates. May produce an allergic reaction.                      In the EU applies: As from 24 August 2023 adequate training is required before industrial or professional use.</p>
Contains	<p>4,4'-methylene diphenyl diisocyanate;                      reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate;                      modified methylene diphenyl diisocyanate</p>

## 2.3 Other hazards

Persons suffering from allergic reactions to this product should avoid contact with de product.

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006.

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006.

# Wisapur<sup>®</sup>-duo 912 Härter

## 3. Composition/information on ingredients

### 3.1 Substances

This product is a mixture, for more see section 3.2.

### 3.2 Description of the mixture

Mixture of the following dangerous substances in quantities to be declared/relevant.

#### Content: 5 % - < 25 %

CAS No.: - EG No.: 905-806-4 Index No.: - Reg. No. (REACH): 01-2119457015-45-XXXX	<b>reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate</b>  SCL Skin Irrit. 2, H315: >=5% SCL Eye Irrit. 2, H319: >=5% SCL Resp. Sens. 1, H334: >=0.1% SCL STOT SE 3, H335: >=5%	Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; Resp. Sens. 1, H334; STOT SE 3, H335; Carc. 2, H351; STOT RE 2, H373
--	--	--

#### Content: 5 % - < 25 %

CAS No.: 25686-28-6 EG No.: 500-040-3 Index No.: - Reg. No. (REACH): 01-2119457013-49-XXXX	<b>modified methylene diphenyl diisocyanate</b>  SCL Skin Irrit. 2, H315: >=5% SCL Eye Irrit. 2, H319: >=5% SCL Resp. Sens. 1, H334: >=0.1% SCL STOT SE 3, H335: >=5% SCL ATE (inhalative, dust/fog): 1.5 mg/l/4h SCL ATE (inhalative, vapours): 11 mg/l/4h	Skin Irrit. 2, H315; Skin Sens. 1, H317; Eye Irrit. 2, H319; Acute Tox. 4, H332; Resp. Sens. 1, H334; STOT SE 3, H335; Carc. 2, H351; STOT RE 2, H373
---	--	--

#### Content: 5 % - < 15 %

CAS No.: 101-68-8 EG No.: 202-966-0 Index No.: 615-005-00-9 Reg. No. (REACH): 01-2119457014-47-XXXX	<b>4,4'-methylene diphenyl diisocyanate</b>  Further name(s): diphenylmethane-4,4'-diisocyanate  SCL Skin Irrit. 2, H315: >=5% SCL Eye Irrit. 2, H319: >=5% SCL Resp. Sens. 1, H334: >=0.1% SCL STOT SE 3, H335: >=5%	Carc. 2, H351; Acute Tox. 4, H332; STOT RE 2, H373; Eye Irrit. 2, H319; STOT SE 3, 335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317
--	---	---

Note: H-phrases and abbreviations are detailed in section 16.

## 4. First aid measures

### 4.1 Description of first aid measures

General information	Observe the general rules of first aid measures. Refresh occasionally your knowledge. If medical advice is required, have this safety data sheet, the packaging or the label ready.
Following inhalation	Remove affected person from the danger area. Supply fresh air. Loosen restrictive clothing. Place in a resting position. Consult a doctor depending on the symptoms. If not breathing provide immediately artificial respiration and obtain medical treatment. In case of unconsciousness bring person in recovery position and take medical advice.
Following skin contact	Product residues remove mechanically, e.g. Remove contaminated clothing immediately. Wash skin with much water and soap. Consult a doctor depending on the symptoms, if possible, show this container or label. If there is one, dab affected body areas with polyethylene glycol 400 (or similar non-hazardous polyol).
Following eye contact	Remove contact lenses, if present and easy to do. Rinse thoroughly with water and consult a doctor. Present this safety data sheet or product label.

# Wisapur®-duo 912 Härter

Following ingestion	Rinse mouth thoroughly with water. Keep airways free. Telephone the emergency number or consult a doctor. If it is possible, present this safety data sheet or product label. Do not induce vomiting! Drink plenty of water. Never give anything by mouth to an unconscious person.
---------------------	---

## 4.2 Most important symptoms and effects, both acute and delayed

It may, in particular through prolonged or repeated exposure the following symptoms may occur. Dermatitis (inflammation), desiccation of the skin, allergic contact eczema, skin discolouration, Irritation in the nasal and pharyngeal mucous membranes, cough, Headaches, effects on the central nervous system, asthmatic symptoms, shortness of breath.

In certain cases, symptoms of intoxication may only appear after a longer period of time/after several hours.

## 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment

In pulmonary irritation treat initially with dexamethasone metered-dose aerosol. Pulmonary edema prophylaxis.

Medical examinations required because delayed entering effective possible.

## 5. Firefighting measures

### 5.1 Extinguishing media

Always adapt firefighting measures to the surroundings and the size of the fire.

Suitable extinguishing media: Water spray jet, Dry powder fire extinguishers, Alcohol-resistant foam, Carbon dioxide
--

Unsuitable extinguishing media: Full water jet
--

### 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire:

Carbon oxide (Carbon monoxide, ..), Nitrogen oxide (NOx), Isocyanat, Hydrocyanic acid (Hydrogen cyanide), Toxic gases.

Risk of bursting when heated.

### 5.3 Advice for fire-fighters

Do not inhale combustion gases.

Wear breathing apparatus with own air supply. Wear full protection depending on fire class.

Use water spray to cool endangered containers.

Dispose contaminated fire extinguishing water according to official directives.

## 6. Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Arrange for sufficient air supply. Avoid eye and skin contact as well as inhalation. Keep away unnecessary people from the scene of an accident; ideally contrary to the wind direction. Wear protective clothing (see Section 8).

### 6.2 Environmental precautions

Avoid further leakage or release, if it's possible without risk. Do not empty into drains. Prevent surface and ground-water infiltration, as well as ground penetration.

### 6.3 Methods and material for containment and cleaning up

Absorb bigger quantities with fluid-binding material (e.g. universal binder, sand, diatomaceous earth, sawdust) and dispose of according to section 13.

Let stand for several days until no further reaction in an unsealed container. Keep moist. Do not close the container. CO2 formation in closed containers can print arise.

### 6.4 Reference to other sections

Personal protective equipment see section 8. Waste disposal see section 13.

## 7. Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation. Avoid inhaling the vapors. If necessary suction measures at the workplace or on the processing machines required. With allergies, asthma and chronic respiratory diseases, no contact with products of this kind. Open and handle receptacle with care. Avoid eye and skin contact. Eating, drinking, smoking, as well as food-storage, is prohibited in workspace. Notes note on the packaging and current technical data sheet. Use

# Wisapur®-duo 912 Härter

working methods according to operating instructions. Avoid release into the environment. Put on appropriate protective equipment (see section 8). Wash contaminated clothing before reuse. General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and after work. Take off contaminated clothing and protective equipment before entering eating areas.

## 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well-ventilated place.

To avoid the unauthorized and children and kept in a safe place. Do not store warnings in corridors and stairwells. Store only in original container and keep locked up. Store this material from incompatible materials. Keep away from food, drink and animal feedingstuffs. Protect them from direct sunlight and heat. Store in a dry place. Protect the product against moisture.

Recommended storage temperature: +15°C - +25°C.

## 7.3 Specific end uses

Adhesive - See technical data sheet and the product imprint.

## 8. Exposure controls/personal protection

### 8.1 Control parameters

Components with limit values that require monitoring at the workplace:

<p><b>Isocyanate limit values</b></p> <p>General limit values for diisocyanates, polymeric isocyanate and reaction masses with isocyanates</p>	<p>CH: MAC: 0.005 ppm (0.02 mg/m<sup>3</sup>) (measured as total NCO)                  CH: STEL: 0.005 ppm (0.02 mg/m<sup>3</sup>) (measured as total NCO)                  CH: 10 µg/g (5 nmol/mmol) Kreatinin (4,4'-Diaminodiphenylmethan, U, b)                  DE: TWA: 0.05 mg/m<sup>3</sup> (up to 31.12.2028) (calculated as MDI)                  EU: TWA: 10 µg/m<sup>3</sup> (up to 31.12.2028) (measured as NCO, diisocyanates) (EU)                  EU: TWA: 6 µg/m<sup>3</sup> (from the 01.01.2029) (measured as NCO, diisocyanates) (EU)                  Peak Limitation – Exceedance Factor: 1,=2=(I) (calculated as MDI)                  BLV: 10 µg/g Kreatinin (4,4'-Diaminodiphenylmethan, U, b), (4,4'-MDI)                  Other information: DFG, H, Y (calculated as MDI) (AGW) / (diisocyanates) (EU)                  AT: MAC-TWA / TRC-TWA: 0.005 ppm (0.05 mg/m<sup>3</sup>) (4,4'-MDI)                  AT: MAC-TWA: 10 µg/m<sup>3</sup> (up to 31.12.2028) (measured as NCO, diisocyanates) (EU)                  AT: MAC-TWA: 6 µg/m<sup>3</sup> (from the 01.01.2029) (measured as NCO, diisocyanates) (EU)                  AT: MAC-STV / TRC-ST: 0.01 ppm (0.1 mg/m<sup>3</sup>) [8 x 5min. (Mow)] (4,4'-MDI)                  The specific measurement methods must be agreed with the provider carrying out the measurements.</p>
<p>CAS No.: -                  EG No.: 905-806-4                  Index No.: -                  Reg. No. (REACH): 01-2119457015-45-XXXX</p>	<p><b>reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate</b></p> <p>CH: MAC: 0.005 ppm (0.02 mg/m<sup>3</sup>)                  Mehr Informationen siehe <b>Isocyanat-Grenzwerte</b> unter Abschnitt 8.1</p>
<p>CAS No.: 25686-28-6                  EG No.: 500-040-3                  Index No.: -                  Reg. No. (REACH): 01-2119457013-49-XXXX</p>	<p><b>modified methylene diphenyl diisocyanate</b></p> <p>CH: MAC: 0.005 ppm (0,02 mg/m<sup>3</sup>)                  Mehr Informationen siehe <b>Isocyanat-Grenzwerte</b> unter Abschnitt 8.1</p>
<p>CAS No.: 101-68-8                  EG No.: 202-966-0                  Index No.: 615-005-00-9                  Reg. No. (REACH): 01-2119457014-47-XXXX</p>	<p><b>4,4'-methylene diphenyl diisocyanate</b></p> <p>CH: MAC: 0.005 ppm (0.02 mg/m<sup>3</sup>)                  DE: TWA: 0.05 mg/m<sup>3</sup> E                  Mehr Informationen siehe <b>Isocyanat-Grenzwerte</b> unter Abschnitt 8.1</p>
<p>CAS No.: 7631-86-9                  EG No.: 231-545-4                  Index No.: -</p>	<p><b>silicon dioxide</b></p> <p>CH: MAC: 4 mg/m<sup>3</sup> (e)</p>

# Wisapur®-duo 912 Härter

Reg. No. (REACH): 01-2119379499-16-XXXX	DE: TWA: 4 mg/m <sup>3</sup> E
CAS No.: 21645-51-2 EG No.: 244-492-7 Index No.: - Reg. No. (REACH): -	<b>aluminium hydroxide</b> CH: MAC: 3 mg/m <sup>3</sup> (a) EU: TWA: 10 mg/m <sup>3</sup> (alveolar fraction) EU: TWA: 1.25 mg/m <sup>3</sup> (inhalable fraction) [25/SQ,1/5]
<p>MAK = Maximum Workplace Concentration (TLV = Threshold Limit Value)          CH It's a swiss limit, edited by SUVA. If there is no limit from SUVA it's a work place limit (AGW) from Germany or another European state.</p>	
CAS No.: 25686-28-6 EG No.: 500-040-3 Index No.: - Reg. No. (REACH): 01-2119457013-49-XXXX	<b>modified methylene diphenyl diisocyanate</b> employee: DNEL: 0.1 mg/m <sup>3</sup> [inhalative, short-term, systemic effects]; employee: DNEL: 28.7 mg/cm <sup>2</sup> [dermal exposure route, long-term, systemic effects]; employee: DNEL: 0.1 mg/m <sup>3</sup> [inhalative, short-term, local effects]; employee: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, long-term, systemic effects]; employee: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, long-term, local effects]; employee: DNEL: 50 mg/kg [dermal exposure route, short-term, systemic effects]; consumer: DNEL: 25 mg/kg [dermal exposure route, short-term, systemic effects]; consumer: DNEL: 20 mg/kg [oral, short-term, systemic effects]; consumer: DNEL: 17.2 mg/cm <sup>2</sup> [dermal exposure route, long-term, systemic effects]; consumer: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, short-term, local effects]; consumer: DNEL: 0.025 mg/m <sup>3</sup> [inhalative, long-term, systemic effects]; consumer: DNEL: 0.025 mg/m <sup>3</sup> [inhalative, long-term, local effects]; consumer: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, short-term, systemic effects]; environment: PNEC: 1 mg/l [microorganisms in wastewater treatment plants]; environment: PNEC: 0.0037 mg/l [fresh water]; environment: PNEC: 0.00037 mg/l [sea water]; environment: PNEC: 37 mg/l [freshwater (intermittent release)]; environment: PNEC: 11.7 mg/kg [sediment, fresh water]; environment: PNEC: 1.17 mg/kg [sediment, seawater]; environment: PNEC: 2.33 mg/kg [soil] [24/Q2/4]
CAS No.: - EG No.: 905-806-4 Index No.: - Reg. No. (REACH): 01-2119457015-45-XXXX	<b>reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate</b> employee: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, short-term, local effects]; employee: DNEL: 0.05 mg/kg [inhalative, long-term, local effects]; consumer: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, short-term, local effects]; consumer: DNEL: 0.025 mg/m <sup>3</sup> [inhalative, long-term, local effects]; environment: PNEC: 37 µg/l [fresh water]; environment: PNEC: 0.37 µg/l [sea water]; environment: PNEC: 3.7 µg/l [water, sporadic release]; environment: PNEC: 1 mg/l [microorganisms in wastewater treatment plants]; environment: PNEC: 11.7 mg/kg [sediment, fresh water]; environment: PNEC: 1.17 mg/kg [sediment, seawater]; environment: PNEC: 2.33 mg/kg [soil] [24/Q2/4]
CAS No.: 25686-28-6 EG No.: 500-040-3 Index No.: - Reg. No. (REACH): 01-2119457013-49-XXXX	<b>modified methylene diphenyl diisocyanate</b> employee: DNEL: 0.1 mg/m <sup>3</sup> [inhalative, short-term, systemic effects]; employee: DNEL: 28.7 mg/cm <sup>2</sup> [dermal exposure route, long-term, systemic effects]; employee: DNEL: 0.1 mg/m <sup>3</sup> [inhalative, short-term, local effects]; employee: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, long-term, systemic effects]; employee: DNEL: 0.05 mg/m <sup>3</sup> [inhalative, long-term, local effects]; employee: DNEL: 50 mg/kg [dermal exposure route, short-term, systemic effects]; consumer: DNEL: 25 mg/kg [dermal exposure route, short-term, systemic effects];

# Wisapur<sup>®</sup>-duo 912 Härter

	<p>consumer: DNEL: 20 mg/kg [oral, short-term, systemic effects];          consumer: DNEL: 17.2 mg/cm<sup>2</sup> [dermal exposure route, long-term, systemic effects];          consumer: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, short-term, local effects];          consumer: DNEL: 0.025 mg/m<sup>3</sup> [inhalative, long-term, systemic effects];          consumer: DNEL: 0.025 mg/m<sup>3</sup> [inhalative, long-term, local effects];          consumer: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, short-term, systemic effects];          environment: PNEC: 1 mg/l [microorganisms in wastewater treatment plants];          environment: PNEC: 0.0037 mg/l [fresh water];          environment: PNEC: 0.00037 mg/l [sea water];          environment: PNEC: 37 mg/l [freshwater (intermittent release)];          environment: PNEC: 11.7 mg/kg [sediment, fresh water];          environment: PNEC: 1.17 mg/kg [sediment, seawater];          environment: PNEC: 2.33 mg/kg [soil] [24/Q2/4]</p>
<p>CAS No.: 101-68-8          EG No.: 202-966-0          Index No.: 615-005-00-9          Reg. No. (REACH): -</p>	<p><b>4,4'-methylene diphenyl diisocyanate</b>          employee: DNEL: 50 mg/kg bw/d [dermal exposure route, short-term, systemic effects];          employee: DNEL: 0.1 mg/m<sup>3</sup> [inhalative, short-term, systemic effects];          employee: DNEL: 28.7 mg/cm<sup>2</sup> [dermal exposure route, long-term, systemic effects];          employee: DNEL: 0.1 mg/m<sup>3</sup> [inhalative, short-term, local effects];          employee: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, long-term, local effects];          employee: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, long-term, systemic effects];          consumer: DNEL: 25 mg/kg bw/d [dermal exposure route, short-term, systemic effects];          consumer: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, short-term, systemic effects];          consumer: DNEL: 20 mg/kg bw/d [oral, short-term, systemic effects];          consumer: DNEL: 17.2 mg/cm<sup>2</sup> [dermal exposure route, long-term, systemic effects];          consumer: DNEL: 0.05 mg/m<sup>3</sup> [inhalative, short-term, local effects];          consumer: DNEL: 0.025 mg/m<sup>3</sup> [inhalative, long-term, systemic effects];          consumer: DNEL: 0.025 mg/m<sup>3</sup> [inhalative, long-term, local effects];          environment: PNEC: 11.7 µg/l [fresh water];          environment: PNEC: 1.17 mg/l [sea water];          environment: PNEC: 570.4 mg/kg [sediment, fresh water];          environment: PNEC: 57.04 mg/kg [sediment, seawater];          environment: PNEC: 2.33 mg/kg dw [soil];          environment: PNEC: 1 mg/l [microorganisms in wastewater treatment plants];          environment: PNEC: 37 mg/l [water, sporadic (intermittent) release] [24/Q2/4]</p>
<p>CAS No.: 7631-86-9          EG No.: 231-545-4          Index No.: -          Reg. No. (REACH): 01-2119379499-16-XXXX</p>	<p><b>silicon dioxide</b>          employee: DNEL: 4 mg/m<sup>3</sup> [inhalative, long-term, local effects]</p>
<p>CAS No.: 21645-51-2          EG No.: 244-492-7          Index No.: -          Reg. No. (REACH): -</p>	<p><b>aluminium hydroxide</b>          consumer: DNEL: 10.76 mg/m<sup>3</sup> [inhalative, long-term, local effects];          consumer: DNEL: 10.76 mg/m<sup>3</sup> [inhalative, long-term, systemic effects];          consumer: DNEL: 4.74 mg/kg bw/d [oral, short-term, systemic effects] [25/Q2/2]</p>
<p>CAS No.: 1318-02-1          EG No.: 930-915-9          Index No.: -          Reg. No. (REACH): 01-2119429034-49-XXXX</p>	<p><b>zeolite</b>          employee: DNEL: 2.5 mg/kg bw/d [dermal exposure route, long-term, systemic effects];          employee: DNEL: 3 mg/m<sup>3</sup> [inhalative, long-term, local effects];          consumer: DNEL: 1.25 mg/kg bw/d [oral, long-term, systemic effects];          consumer: DNEL: 1.25 mg/kg bw/d [dermal exposure route, long-term, systemic effects];          environment: PNEC: 3.2 mg/l [fresh water];          environment: PNEC: 0.32 mg/l [sea water];          environment: PNEC: 600 mg/kg [soil];          environment: PNEC: 95 mg/l [microorganisms in wastewater treatment plants] [24/Q2/1]</p>

# Wisapur<sup>®</sup>-duo 912 Härter

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation, e.g. by local suction, general exhaust air.  
 Minimize the risk of inhalations of vapours.  
 If possible, work with completely self-contained equipment.  
 Comply with the workplace exposure limits.  
 If limits can't be adhered to, use appropriate respiratory protection.

### 8.2.2 Personal protective equipment

General data	Select personal protective equipment according to the CEN standards; discuss protective equipment with the supplier.
Eye/face protection	Safety glasses with side protection shield (EN 166).
Hand-/Body protection	Use chemical-resistant protective gloves according to EN 374.
Protective clothing	Wear suitable protective clothing, e.g long-sleeved clothes and safety shoes according to EN ISO 20345.
Respiratory protection	Normally not needed. Comply with the workplace exposure limits. Use self-contained breathing apparatus. Filter A2 P2 according to EN 14387 (Colour code brown, white). Follow the wear time limits for breathing apparatus.
Hygiene measures	General hygiene measures for the handling of chemicals are applicable. Do not eat, drink or smoke while at work. Wash hands before breaks and after work.
Thermal hazards	Not applicable.



On the basis of the contents and our experience the following non-binding recommendations for the selection of the material of the protective gloves (minimum layer thickness: 0.4 mm):

Recommended glove material:	Nitrile rubber/Nitrile latex (NBR)
Inappropriate glove material:	Textile Materials

The selection of suitable depends upon the material, and also upon the quality of the gloves. The degree of protection will vary from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the materials used for gloves cannot be predetermined; it is therefore necessary to check this before using the product.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

### 8.2.3 Environmental exposure controls

More information that is detailed is not available yet.

## 9. Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	Pasty
Colour	beige
Density	~1.55 g/cm <sup>3</sup> (20°)
Viscosity	Low viscosity-pasty
Odour	Characteristic
Odour threshold	Not determined
pH-level	Not determined
Melting point/freezing point	Not determined
Initial boiling point/boiling range	Not determined
Decomposition temperature	Not determined
Rate of evaporation	Not determined
Flashpoint	Not determined
Auto-ignition temperature	Not determined
Lower explosive limits	Not determined

# Wisapur®-duo 912 Härter

Upper explosive limits	Not determined
Vapour pressure	Not determined
Vapour density (Air = 1)	Not determined
Explosive properties	The product is not explosive.
Oxidising properties	No

## 9.2 Other information

Solubility in / Miscibility with water.	Immiscible with water
Solubility in / Miscibility in	Not determined
Partition coefficient n-Octanol/Water	Not determined
Conductivity	Not determined
VOC-content (EU)	0.4% (6.1 g/l)
VOC-content (CH)	0.4% (6.1 g/l)

## 10. Stability and reactivity

### 10.1 Reactivity

This product reacts with water under formation of foam.

### 10.2 Chemical stability

The product is stable when properly stored and handled.

### 10.3 Possibility of hazardous reactions

Exothermic reaction possible with in section 10.5 called incompatible materials.  
CO<sub>2</sub>

### 10.4 Conditions to avoid

Protect from humidity. Protect container from direct sun.  
Polymerization possible at high temperatures.

### 10.5 Incompatible materials

Acids, Bases, Alcohols, Amines, Water.

### 10.6 Hazardous decomposition products

No decomposition if used according to specifications.  
In case of fire or very high heat can i.a. the following hazardous decomposition products are formed:  
Carbon oxide (Carbon monoxide, ..), Nitrogen oxide (NOx), Isocyanat, Hydrocyanic acid (Hydrogen cyanide).

## 11. Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (inhalativ)	ATE >20 mg/l/4h [Calculated value, vapours]
----------------------------	---

### 11.2. Toxicological information of hazardous ingredients

CAS No.: - EG No.: 905-806-4 Index No.: - Reg. No. (REACH): 01-2119457015-45- XXXX	<b>reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate</b> acute toxicity: LD50: >10000 mg/kg [oral, rat]; acute toxicity: LD50: >9400 mg/kg [dermal exposure route, rabbit]; acute toxicity: LC50: 0.49 mg/l/4h [inhalative, rat, fog, dust the EU classification may vary depending on the source or the variant of the substance]; corrosive/irritant effect on the skin: irritant [rabbit, OECD 404]; respiratory/skin sensitization: sensitising (inhalation, skin contact) [Guinea pig, OECD 400]; germ cell mutagenicity: negative [Salmonella typhimurium, (Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)]; germ cell mutagenicity: negative [rat, OECD 474 (Mammalian Erythrocyte Micronucleus Test)]; carcinogenicity: [rat, OECD 453, Carc. 2] [24/Q2/2]
CAS No.: 25686-28-6 EG No.: 500-040-3	<b>modified methylene diphenyl diisocyanate</b> acute toxicity: LD50: >2000 mg/kg [oral, rat, OECD 401, analogy reasoning];

Wisapur<sup>®</sup>-duo 912 Härter

<p>Index No.: - Reg. No. (REACH): 01-2119457013-49-XXXX</p>	<p>acute toxicity: ATE: 11 mg/l/4h [inhalative, vapours]; acute toxicity: ATE: 1.5 mg/l/4h [inhalative, dust/fog]; corrosive/irritant effect on the skin: irritant [rabbit, OECD 404, Skin. Irrit. 2]; serious eye damage/irritation: irritant [rabbit, OECD 405, Skin. Irrit. 2]; respiratory/skin sensitization: irritant [Guinea pig, OECD 406, sensitising (skin contact)]; respiratory/skin sensitization: [mouse, OECD 405, inhalation]; germ cell mutagenicity: negative [OECD 471, Salmonella typhimurium, Regulation (EC) 440/2008 B.13/B.14 (Reverse Mutation Test using Bacteria)]; germ cell mutagenicity: negative [rat, OECD 474 (Mammalian Erythrocyte Micronucleus Test)]; specific target organ toxicity - single exposure (STOT SE): 0.2 mg/m<sup>3</sup> [NOEL: OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)]; symptoms: tearing of the eyes, breathing difficulties, asthmatic complaints, cough [24/Q2/2]</p>
<p>CAS No.: 101-68-8 EG No.: 202-966-0 Index No.: 615-005-00-9 Reg. No. (REACH): -</p>	<p><b>4,4'-methylene diphenyl diisocyanate</b> acute toxicity: LD50: &gt;2000 mg/kg [oral, rat, analogy reasoning]; acute toxicity: LD50: &gt;9400 mg/kg [dermal exposure route, rabbit, OECD 402, analogy reasoning]; acute toxicity: LC50: 0.368 mg/l/4h [inhalative, rat, OECD 403, aerosol, the EU classification may vary depending on the source or the variant of the substance]; acute toxicity: LC50: 1.5 mg/l/4h [inhalative, aerosol]; acute toxicity: ATE: 1.5 mg/l/4h [inhalative, dust/fog]; acute toxicity: ATE: 11 mg/l/4h [inhalative, vapours]; corrosive/irritant effect on the skin: irritant [rabbit, OECD 404, Skin. Irrit. 2, analogy reasoning]; respiratory/skin sensitization: sensitising (inhalation) [Guinea pig]; respiratory/skin sensitization: sensitising (skin contact) [mouse, OECD 429, Skin. Sens. 1]; germ cell mutagenicity: negative [Salmonella typhimurium, OECD 471 (Bacterial Reverse Mutation Test), analogy reasoning]; germ cell mutagenicity: negative [rat, OECD 474 (Mammalian Erythrocyte Micronucleus Test)]; germ cell mutagenicity: negative [rat, OECD 489 (In Vivo Mammalian Alkaline Comet Assay)]; carcinogenicity: [rat, OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies), aerosol, analogy reasoning, Carc. 2]; reproductive toxicity: NOAEL, 4-12 mg/m<sup>3</sup> [rat, OECD 414 (Prenatal Developmental Toxicity Study), aerosol, analogy reasoning]; specific target organ toxicity - single exposure (STOT SE): may irritate the respiratory tract [inhalative]; specific target organ toxicity - repeated exposure (STOT RE): LOAEL, 1 mg/m<sup>3</sup> [rat, OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies), inhalative, analogy reasoning]; symptoms: shortness of breath, cough, mucous membrane irritation [24/Q2/2]</p>
<p>CAS No.: 7631-86-9 EG No.: 231-545-4 Index No.: - Reg. No. (REACH): 01-2119379499-16-XXXX</p>	<p><b>silicon dioxide</b> acute toxicity: LD50: &gt;5000 mg/kg [oral, rat, OECD 423]; acute toxicity: LD50: &gt;2000 mg/kg [dermal exposure route, rat, OECD 402]; acute toxicity: LC50: &gt;0.139 mg/l/4h [inhalative, rat]; corrosive/irritant effect on the skin: non-irritant [rabbit, OECD 404]; serious eye damage/irritation: non-irritant [rabbit, OECD 405]; respiratory/skin sensitization: not sensitising [Guinea pig]; germ cell mutagenicity: negative [OECD 471]; aspiration hazard: no; symptoms: by eye contact: Irritation and redness may occur. [25/Q2/2,4]</p>
<p>CAS No.: 21645-51-2 EG No.: 244-492-7 Index No.: Reg. No. (REACH):</p>	<p><b>aluminium hydroxide</b> acute toxicity: LD50: &gt;2000 mg/kg [oral, rat, female, OECD 423]; acute toxicity: LD50: &gt;5.09 mg/l/4h [inhalative, rat, analogy reasoning, OECD 403]; serious eye damage/irritation: non-irritant [rabbit, OECD 405]; respiratory/skin sensitization: no (skin contact) [Guinea pig, OECD 405]; symptoms: metal fume fever, constipation [25/Q2/2]</p>

# Wisapur<sup>®</sup>-duo 912 Härter

<b>12. Ecological information</b>	
<b>12.1 Toxicity</b>	
Aquatic toxicity Germany (Self-classification)	WGK 1 Slightly hazardous to water
The product is not classified as dangerous for the environment.	
<b>12.2 Persistence and degradability</b>	
The product is not biodegradable.	
<b>12.3 Bioaccumulative potential</b>	
No information is available.	
<b>12.4 Mobility in soil</b>	
No information is available.	
<b>12.5 Results of PBT and vPvB assessment</b>	
See section 2.3.	
<b>12.6 Other adverse effects</b>	
Do not allow product to reach ground water, water course or sewage system.	
<b>12.7 Additional ecotoxicological information</b>	
CAS No.: - EG No.: 905-806-4 Index No.: - Reg. No. (REACH): 01-2119457015-45-XXXX	<b>reaction mass of 4,4'-methylenediphenyldiisocyanate and o-(p-isocyanatobenzyl)phenylisocyanate</b> acute toxicity, fish: LC50: >1000 mg/l/96h [OECD 203]; acute toxicity, daphnia: NOEC/NOEL: >10 mg/l/21d [Daphnia magna, OECD 211]; acute toxicity, daphnia: EC50: >1000 mg/l/24h [Daphnia magna, OECD 202]; acute bacteriotoxicity: EC50: >100 mg/l/3h [activated sludge]; persistence and degradability: 28d, 0% [OECD 302 C, Inherent Biodegradability – Modified MITI Test (II)]; bioaccumulative potential: BCF: 200, is not to be expected [24/Q2/2]
CAS No.: 25686-28-6 EG No.: 500-040-3 Index No.: - Reg. No. (REACH): 01-2119457013-49-XXXX	<b>modified methylene diphenyl diisocyanate</b> acute toxicity, fish: LC50: >1000 mg/l/96h [OECD 203]; acute toxicity, daphnia: NOEC/NOEL: >10mg/l/21d [Daphnia magna, OECD 211]; acute toxicity, algae: EC50: >1640 mg/l/72h [OECD 201]; persistence and degradability: 0%/28, non-biodegradable [OECD 302C]; bioaccumulative potential: BCF: 200, is not to be expected [OECD 305]; acute bacteriotoxicity: EC50: >100 mg/l/3h [OECD 209]; other information: Contains organically bound halogens, which can contribute to the AOX value in waste water. [24/Q2/2]
CAS No.:101-68-8 EG No.: 202-966-0 Index No.: 615-005-00-9 Reg. No. (REACH): -	<b>4,4'-methylene diphenyl diisocyanate</b> acute toxicity, fish: LC50: >1000 mg/l/96h [Brachydanio rerio, OECD 203]; acute toxicity, daphnia: EC50: >1000 mg/l/24h [Daphnia magna, analogy reasoning]; acute toxicity, algae: NOEC/NOEL: 1640 mg/l/72h [Desmodesmus subspicatus, OECD 201, analogy reasoning]; acute toxicity, algae: EC50: 1.5 mg/l/72h [OECD 201]; persistence and degradability: 0%/28d, [OECD 302 C, slowly reacts with water at the boundary surface to form a solid, high-melting insoluble reaction product with the formation of CO <sub>2</sub> . polyurea is inert and non-degradable according to experience to date; bioaccumulative potential: Log Pow: 5.22, is to be expected; bioaccumulative potential: BCF: 200/28d acute bacteriotoxicity: EC50: >100 mg/l/3h [activated sludge, OECD 209, analogy reasoning]; acute toxicity, other organisms: NOEC/NOEL, >1000 mg/kg/14d [Lactuca sativa, OECD 208, analogy reasoning]; acute toxicity, other organisms: NOEC/NOEL, EC50: >1000 mg/kg/14d [Avena sativa, OECD 208, analogy reasoning]; annelid worm toxicity: EC50: >1000 mg/kg/14d [Eisenia foetida, OECD 207];

# Wisapur<sup>®</sup>-duo 912 Härter

	<p>annelid worm toxicity: NOEC/NOEL: &gt;1000 mg/kg/14d [Lumbricus terrestris, OECD 207, analogy reasoning];          mobility in soil: H (Henry): 0.0229 Pa*m<sup>3</sup>/mol [Cyprinus Caprio, is not to be expected];          results of PBT and vPvB assessment: no PBT substance; no vPvB substance;          other information: does not contain organically bound . [24/Q2/2]</p>
<p>CAS No.: 7631-86-9          EG No.: 231-545-4          Index No.: -          Reg. No. (REACH): 01-2119379499-16-XXXX</p>	<p><b>silicon dioxide</b>          acute toxicity, fish: LC0: &gt;10000 mg/l/96h [Brachydanio rerio, OECD 203];          acute toxicity, daphnia: EC0: &gt;1000 mg/l/24h [Daphnia magna, OECD 202];          acute toxicity, algae: ErC50: &gt;10000 mg/l/72h [Scenedesmus Subspicatus, OECD 201];          persistence and degradability: does not apply to inorganic substances.          results of PBT and vPvB assessment: no PBT substance, no vPvB substance          [24/Q2/2]</p>
<p>CAS No.: 21645-51-2          EG No.: 244-492-7          Index No.: -          Reg. No. (REACH): 01-2119529246-39-XXXX</p>	<p><b>aluminium hydroxide</b>          acute toxicity, fish: LC50: &gt;100 mg/l/96h [Salmo trutta-fario, OECD 203];          acute toxicity, daphnia: EC50: &gt;100 mg/l/48h [Daphnia magna, OECD 202];          acute toxicity, algae: EC50: &gt;100 mg/l/72h [Selenastrum capricornutum, OECD 201] [25/Q2/5]</p>

## 13. Disposal considerations

### 13.1 Waste treatment methods

Waste disposal according to official state regulations.

Waste treatment options:

08 04 09 – Waste adhesives and sealants containing organic solvents or other dangerous substances.

08 05 01 – waste isocyanates

Contaminated packages:

Disposal must be made according to official regulations. If possible empty packaging completely.

CH: After complete hardening, product can be disposed of with domestic waste.

Packagings that cannot be cleaned are to be disposed off in the same manner as the product.

Alternatively, it can be used if necessary following waste code: 15 01 10 – Packing that contains the residues of hazardous materials or is contaminated through hazardous materials.

- The waste code numbers mentioned are recommendations based on the probable use of the product. The particular application and local disposal situation obtaining for the user may lead to other waste codes being assigned as well.
- Switzerland: Following regulation in the latest valid constitution must be observed: Technical regulation on waste (TVA, SR 814.600), regulation for waste processing (VeVa, SR 814.610) and in the regulation of UVEK concerning lists for handling waste (LVA, SR 814.610.1).

## 14. Transport information

### 14.1 UN-Number:

ADR, RID, ADN, IMDG, IATA: Not applicable

### 14.2 UN proper shipping name

ADR, RID, ADN, IMDG, IATA: Not applicable

### 14.3 Transport hazard class(es):

ADR, RID, ADN, IMDG, IATA: Not applicable

### 14.4 Packing group:

ADR, RID, ADN, IMDG, IATA: Not applicable

### 14.5 Environmental hazards:

Dangerous to the environment: No

Marine pollutant: No

# Wisapur<sup>®</sup>-duo 912 Härter

## 14.6 Special precautions for user:

Kemmler number:	Not applicable
EMS number:	Not applicable

## 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Inapplicable

## 14.8 Additional information:

ADR: LQ – Limited Quantities:	Not applicable
ADR: Transport category:	Not applicable
ADR: Tunnel restriction code:	Not applicable
UN „Model Regulation“:	Inapplicable

## 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substances or mixture

Classification and labelling see section 2.

The classification is based on the calculation method, unless otherwise stated.

Further national and further regulations, limitations and legal requirements

VOC content according to swiss VOC regulation (VOCV) see section 9.2.
Water hazard class (WGK) see section 12.1.
Observe employment restrictions for young people (CH: SR 822.115).
Observe Mutterschutzgesetz (DE) bzw. Mutterschutzverordnung (CH: SR 822.111.52).
Chemicals regulation (ChemV), ordinance on chemicals risk reduction (ChemRRV), Luftreinhalte-Verordnung (LRV), Ordinance on protection against major accidents (StfV), professional association principles/industrial medicine regulations

### 15.2 Chemical Safety Assessment

A chemical safety assessment is not provided for mixtures.

## 16. Other information

### Hazards used in the document (H-phrases):

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 May probably cause cancer.
H373 May cause damage to organs through prolonged or repeated exposure through inhalation (airways).

### Other recommended sources for more information:

- Federal Office of Public Health (Switzerland): [www.bag.admin.ch](http://www.bag.admin.ch) (German/French/Italian/English)

### List of relevant abbreviations that may be used in the document:

Abbreviation	Full text / Meaning
ADR	Accord européen relatif au transport international des marchandises Dangereuses par Route (= European agreement concerning the international carriage of dangerous goods by road)
AGW, Spb.-Üf.	AGW = Arbeitsplatzgrenzwert (occupational limit value), Spb.-Üf. = Spitzenbegrenzung (peak limit) – Überschreitungsfaktor (exceedance factor) (1 bis 8) and category (I, II) for short-term values (TRGS 900, Germany)
AOEL	Acceptable Operator Exposure Level
Aquatic Acute	Hazardous to the aquatic environment - Acute
Aquatic Chronic	Hazardous to the aquatic environment – Chronic
Asp. Tox.	Aspiration hazard (Danger when inhaling)
ATE	Acute Toxicity Estimates
BAG	Office for health (Bundesamt für Gesundheit, Schweiz)
BAT	Biological tolerance values at the workplace (Biologische Arbeitsstofftoleranzwerte, Schweiz)
BG	Trade association (Berufsgenossenschaft)
BGR	Trade association regulations (Berufsgenossenschaftliche Regeln)
BGV	Trade association regulations (Berufsgenossenschaftliche Vorschrift)
Carz.	Carcinogenic substance
CAS-Nr.	Chemical Abstracts Service
CH	Swiss confederation (from the latin Confoederatio Helvetica)

# Wisapur<sup>®</sup>-duo 912 Härter

CH: MAK:	Swiss limit of maximum allowable concentration, issued by the swiss accident insurance fund. (Schweizerischen Unfallversicherungsanstalt (SUVA))
CLP	Classification, Labelling and Packaing (REGULATION (EG) Nr. 1272/2008)
CPID	Chemical Product IDentification.
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
EG-Nr.	Substances of the EC material inventory, consisting of 7 digits (Syntax: XXX-XXX-X). Comprises waste materials (EINECS), new substances (ELINCS) as well as the No-Longer-Polymers-Liste (NLP-Liste).
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
Eye Irrit.	Eye irritant, depending on the category Eye irritation possible to serious eye damage.
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
Flam. Sol.	Flammable solid
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
IATA	International Air Transport Association
IMDG-Code	International Maritime Code for Dangerous Goods
Index-Nr.	Indexation of dangerous substances of appendix 5 in the VO(EG)1272/2008 (or annex I of directive 67/548/EWG) with the following syntax: XXX-XXX-XX-X
LC	Lethal concentration
LD	Lethal (fatal) dose
LD50	Lethal dose, 50%
Met. Corr.	On metal corrosive acting substance or mixture
Muta.	Substance with germ cell mutagenicity
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
Ozone	Hazardous for the ozone layer
PBT	Persistent, bioaccumulative, and toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals (Verordnung (EG) Nr. 1907/2006 zur Registrierung, Bewertung, Zulassung und Beschränkung chemischer Stoffe)
Repr.	Reproductive toxicity
Resp. Sens.	Sensitising for respiratory tract
SCL	Specific concentration limits
Skin Irrit.	Skin irritant – corrosive/irritant to skin
Skin Sens.	Sensitising for the skin
STOT RE	Specific target organ toxicity – repeated exposure
STOT SE	Specific target organ toxicity – single exposure
TRGS	Technical rules on hazardous substances
VOC	Volatile organic compounds
VOCV	VOC-regulation (Swiss)
vPvB	Very persistent and very bioaccumulative

**Department issuing data specification sheet: See section 1.3.**

This safety data sheet replaces all previous versions.

**Disclaimer:** The specifications rest on the today's stand of our knowledge. It does not constitute a legally binding assurance of specific product properties.

© **Wisabax AG** - Any publication/modification requires written approval from Wisabax AG. Created with the help of SDS (Safety Data Sheets), an in-house software solution designed to simplify the creation of multilingual SDS.